

## 45KVA Mobile Temporary Power Distribution System - 600V to 208Y/120V - (40) 120V 5-20R GFCI Outlets

### MGS-600V-45KVA-40X120



#### 1MGS-600V-45KVA-40X120 Power Transformer

1#000000Line-In Cord: 20' 6/4 SOOW

1#000000Primary Voltage: 600V 3P

1#000000Primary Disconnect: 60A Fused @ 60A

1#000000Transformer: 45KVA 600V-3P to 208Y/120V 3P N3R

1Secondary Panel: 208/120V 3P N3R 150A

1Secondary Breakers: (20) 20A [120V RCPT]

141Secondary Panel Outlets: (40) 5-20R Duplex [120V] - All w/ Weatherproof covers

141Protection: 1GFCI Outlets, Circuit Breakers

141Form Factor: Square tube frame w/ skid pockets, top pick eye & locking 8" casters

141Dimensions: 34"-L X 40"-W X 58"-H

141Weight: 1000lbs

1Larson Electronics manufacture a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

#### 1Ratings

1UL 1640 Portable Power-Distribution Equipment

1NEMA 3R Indoor or Outdoor Use

1Made in the USA

1#000000Max Primary OCP: 60A @ 600V

1#000000Max Secondary OCP: 125A @ 208V

#### 1Special Orders- Requirements

1Contact us for special requirements

1Toll Free: 11-800-369-6671

1Intl: 11-903-498-3363

1E-mail: [1sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

141\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [DimensionalDrawing](#)
- [large](#)
- [Manual](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)