

EPEXC-CO-2-GFI-2-12.3-EPP

20-Amp Explosion Proof Extension Cord - 4' 12/3 SOOW - EXP Proof Plug & Connector w/ Inline EXP GFCI

Product ID: 147311

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPEXC-CO-2-GFI-2-12.3-EPP

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPEXC-CO-2-GFI-2-12.3-EPP Explosion Proof Extension Cord

Unit Type: Explosion Proof Extension Cord w/ Inline GFCI

Amp Rating: 20 Amp Continuous Service

Dimensions: Cord Length - 4 Feet, Plug - 2.78"-L 1.75"-W

Configuration: 2 Pole 3 Wire

Voltage: 125V

Cord Cap: 5-20P or 6-20P EXP

Wiring: 2' 12/3 SOOW Cord w/ (1) Explosion Proof 20A Male Plug and 2' 12/3 SOOW Cord w/ (1) Explosion Proof 20A Connector

GFCI Trip Setting: 5mA

Connector: 5-20C or 6-20C EXP

Receptacle Specs: 1 Inline Receptacle

Materials: Copper Free Aluminum

Mating Plugs: [EPP-15A](#), [EPP-20A](#)

Finish: Epoxy Powder Coat

Plug / Outlet Certifications

Class I, Divisions 1 & 2, Groups C & D

Class II, Divisions 1 & 2, Group F

[U.L. Certification](#)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPEXC-CO-2-GFI-2-12.3-EPP explosion proof extension cord allows operators to safely extend the range of their explosion proof light or equipment cords beyond the boundaries of the hazardous work area. Equipped with Class I/II, Division 1 & 2 plug and connector, this unit is approved for use with explosion proof equipment within classified environments. An inline explosion proof GFCI located at the center of the four-foot explosion proof cord provides protection from electrical shock.

This explosion proof extension cord is constructed of 4' 12/3 SOOW cord and rated at 20 amps of continuous service. The cord is chemical/abrasion resistant and comes with an explosion proof, 20-amp male plug (5-20P or 6-20P) at one end, which measures 2 feet. At the center of the cord, an explosion proof GFCI w/ handle is available for protection against possible injury due to unwanted ground faults. Upon detecting a ground fault current during operation, the unit will trip, interrupting power. The other end of the cord measures 2 feet and is equipped with an explosion proof connector (5-20C or 6-20C). The plug on this cord can only be used in T-style outlets and will not work in standard electrical outlets.

The plugs on these units are of a twist lock design. In order for a secure and working connection to take place, the operator must insert the plug and twist until it locks into place. This ensures a safe seal is made before any sparks from electrical contact can take place. To ensure the highest safety, operators should make connections outside of the hazardous area.

The receptacle is constructed of non sparking aluminum and finished with an epoxy powder coating for durability and added corrosion resistance. The internal receptacle plug contacts are constructed of brass and designed to maintain constant pressure along their entire length for superior connectivity. The plug receptacle is deeply recessed to prevent accidental contacts and designed for twist lock plug insertion to provide secure connections. A neoprene seal fitted inside the connector receptacle seals against the plug when inserted to provide positive sealing against water ingress. A spring loaded receptacle door provides an automatic weather-tight seal when the plug is removed. This flip-style lid features a special notch, allowing operators to lock the door in the open position while plugging or unplugging devices. With no devices plugged into the connector, the lid will screw shut, providing a NEMA 4X seal. When a plug is installed in this connector, the internal seals provide a NEMA 3 seal.

Click Photos to Enlarge

These explosion proof extension cords are preconfigured in 125V (left) or 250V (right). Each unit is equipped with a 20 amp explosion proof cord cap and rated for 20 amps of continual service. The outlets are a twistlock design. The deep recessed contacts in the receptacle housing prevents ordinary and wet location plugs from activating the explosion proof outlets.



125V 5-20P Explosion Proof Straight
Blade Plug



250V 6-20P Explosion Proof Straight
Blade Plug



Outlet accepts EPP-15A and EPP-20A
explosion proof plugs

We offer this unit in a 125V configuration. Each receptacle's contacts are deep recessed to avoid accidental contact and will accept standard non explosion proof plugs that are NEMA 5-20R, or 6-20R compatible although explosion proof plugs must be used to preserve explosion proof approval in hazardous environments. Ordinary location plugs will NOT activate this cord's explosion proof receptacles. This explosion proof connector is a mate for the Larson Electronics EPP-15A and EPP-20A explosion proof plugs and is compatible with all the Larson Electronics explosion proof lights we make with an explosion proof plug. This unit's receptacle is designed to safely contain any arcs between the internal contacts that may be created within the receptacle housing.

Inter-Compatibility: These cords use T style plugs and will work with non-explosion proof standard receptacles and plugs (NEMA 5-15R, 5-20R, or 6-20R) but will not work with standard 120V wall outlets. The included plugs and receptacle are cross-interchangeable with Crouse Hind™ part# ENP5201 plugs and receptacles and Hubble-Killiark part# UGP-20231 ACCEPTOR® plugs and receptacles. Any equipment requiring these C-H or H-B plugs should work with these cords. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Explosion Proof Light Fixtures, Grinders, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: EPEXC-CO-2-GFI-2-12.3-EPP



Image: EPEXC-CO-2-GFI-2-12.3-EPP

EPEXC-CO-2-GFI-2-12.3-EPP

Product ID: 147311

Warranty: 36 Months.

Export Control Classification Number (ECCN): EAR99

Options:

EPEXC-CO-2-GFI-2-12.3-EPP-Cord Cap

Example: EPEXC-CO-2-GFI-2-12.3-EPP-2023-125V

Cord Cap	
5-20	-2023-125V
6-20	-2023-250V

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(<https://www.larsonelectronics.com/images/product/CECCert/147311.PDF>)
- **CE Certificate**(<https://www.larsonelectronics.com/images/product/CECert/147311.PDF>)
- **Certificate 1, Misc**(<https://www.larsonelectronics.com/images/product/Cert1/147311.PDF>)
- **Certificate 2, Misc**(<https://www.larsonelectronics.com/images/product/Cert2/147311.PDF>)
- **Certificate 3, Misc**(<https://www.larsonelectronics.com/images/product/Cert3/147311.PDF>)
- **MSDS (Material Safety Data Sheet)**(<https://www.larsonelectronics.com/images/product/Msds/147311.PDF>)
- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/147311.PDF>)
- **RoHS Certificate (Restriction of Hazardous Substances)**(<https://www.larsonelectronics.com/images/product/RoHSCert/147311.PDF>)
- **SpecSheetSpanish**(<https://www.larsonelectronics.com/images/product/SpecSheetSpanish/147311.PDF>)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(<https://www.larsonelectronics.com/images/product/NECCert/147311.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/147311.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/147311.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/147311.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/147311.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)