

IDCMR-IP-WF-4MP-SFC-25-1227

Wireless Network IP Camera - 4.0MP Resolution - 20FPS - Low Light IR Array - Wireless Transmission

Product ID: 147571

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IDCMR-IP-WF-4MP-SFC-25-1227 Network IP Camera

Unit Type: Network IP Camera
Camera Dimensions: 2.625" H x 6.0" D
Camera Weight: 2 lbs
Watts: 5W (Max)
Voltage: 120-277V AC
Power Source: PoE (802.3af)
Image Sensor: 1/3" Progressive Scan CMOS sensor
Video Resolution: 4.0MP (2688*1520)
Frame Rate: Up to 20fps @ 2688*1520 Resolution
Compression Type: H.264, H.264 OVC, MJPEG
Bit Rate: 32Kbps - 16Mbps
Focal Length: 4mm
Max Field of View: 83°
Shutter Speed: 1/3s to 1/10,000s
Min. Illumination: 0.01 lux (Color) / 0 lux (IR)
IR Range: 65 ft
Day/Night: True D/N w/Mechanical Cut Filter
Digital Noise Reduction: 3D DNR
Ethernet Interface: RJ45
Ethernet Speed: 10/100
Protocols: TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration: Yes
Ambient Temperature Range: -22°F to +140°F

Quick Summary

IP66 Rated
Weatherproof Camera
NEMA 1 Enclosure (Indoor Use)
Wireless Footage Transmission
5.8 GHz Antennae (150 Mbps TR)
Integrated Smart IR LEDs

Special Orders - Special Requirements

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Housing Materials: Aluminum Body, Plastic Sunshield

Lens Material: Tempered Glass

Mounting: Surface Mount

Cord: 25` 16/3 SOOW Cable

Cord Cap Options: 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist. UK BS1363, Intl. Schuko, Pigtail

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Frequently Asked Questions (FAQ)

IDCMR-IP-WF-4MP-SFC-25-1227

Product ID: 147571

Export Control Classification Number (ECCN): EAR99

Options:

IDCMR-IP-WF-4MP-SFC-25-1227-**Cord Cap**

Example: IDCMR-IP-WF-4MP-SFC-25-1227-**5.15**

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UKBS1363	-BS1363
INTL SCHUKO	-Schuko
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- [HigResPic1](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)