Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-SM-24-10.3-15C

24" Electric Explosion Proof Fan on Stand - 7980 CFM - Pedestal Mount - 15' 10/3 SOOW Cord - C1D1

Product ID: 147617

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-SM-24-10.3-15C Hazardous Location Fan
Unit Type: Hazardous Location Fan (Circular Pedestal)
Dimensions: 24" (Blade Diameter)
Weight: 78 lbs
Voltage: 115V or 208-230V
Start-up Amps: 9.8A @ 115V, 4.9A @ 208-230V
Motor: 0.50 Horsepower
Phase: 1
Rotations Per Minute (RPM): 1,725
Blade Pitch: 14 Degrees
CFM Delivery: 7,980
Blade Material: Aluminum
Fan Material/Finish: Powder Coated Steel
Wiring: 15` 10/3 SOOW Cable with Explosion Proof Plug
Cord Cap: 5-15P (115V), 5-20P (115V), 6-20P (208-230V)
Blade/Fan Color: Metallic/Black

Ratings
Class I, Division 1
Class II, Division 1
Direct Drive
Thermal Protection
Made in the USA

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in Texas

The EPF-SM-24-10.3-15C from Larson Electronics is a Hazardous Location Fan that is designed as a spot cooling fan for use in hazardous atmospheres. This Class I Division 1, Class II Division 1 fan is rated for use in atmospheres that include flammable or explosive vapors, gas, or dusts. Three aluminum fan blades angled at 14 degrees (pitch) offer direct cooling in hazardous

locations. The EPF-SM-24-10.3-15C 24" circulation fan comes with a 15` 10/3 SOOW cable and an explosion proof plug for connection to power sources.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT
This hazardous location fan is equipped with a robust design that is intended to minimize ignition or explosion in the applicable hazardous environment. It is important to note that no fan can be completely explosion proof. However, the EPF-SM-24-10.3-15C hazardous location fan has all the design elements that minimize that risk including aluminum blades and a thermally protected, maintenance-free 1/2 HP motor. This hazardous location pedestal fan has a 24" diameter and generates over 7,980 CFM of air output for efficient spot cooling. The EPF-SM-24-10.3-15C fan is available in 115V operating at 9.8 amps or 208-230V operating at 4.9 amps. The powder coated steel fan guards offer corrosion resistance and a high degree of durability while the heavy-duty pedestal stand offers a sturdy base. This explosion proof fan weighs 78 pounds, spins at 1,725 RPM and is equipped with 15` of 10/3 SOOW cable and explosion proof plug.
Cord Options: The Larson Electronics EPF-SM-24-10.3-15C hazardous location fan is outfitted with 15` of 10/3 SOOW cable and an explosion proof plug. The 115V model is available with a 5-15 or 5-20 explosion proof plug while the 208-230V model has a 6-20 explosion proof plug.

Click Photos to Enlarge



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring & Plug: This hazardous location fan is equipped with 15 feet of 10/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-15 15 amp straight blade plug for use with 120V explosion proof outlets, a 5-20 20 amp straight blade plug for use with 120V explosion proof outlets, or a 6-20 20 amp straight blade plug for use with 220-240V explosion proof outlets.
Applications: Hazardous locations, industrial sites, oil and gas facilities, processing plants, construction, aerospace facilities, indoor/outdoor cooling systems and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-SM-24-10.3-15C

Product ID: 147617

Export Control Classification Number (ECCN): EAR99

Options:

EPF-SM-24-10.3-15C-Cord Cap

Example: EPF-SM-24-10.3-15C-1523

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **SpecSheetSpanish**
- **STEP File (3D CAD Model)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **HigResPic10**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**