

LEDVCPL-550-WCM-3480

55 Watt Vandal Resistant LED Garage Light - 347/480V AC - IP65 Rated

Product ID: 147644

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDVCPL-550-WCM-3480 Wall Pack Light

Listing: United States - Canada

Lamp Type: LED

Dimensions (Inches): 11 1/4"-L x 15"-W x 11 1/4"-H

Dimensions (CM): 31.1-L x 40.6-W x 31.1-H

Weight: 7.9 Lbs.

Voltage: 347/480 Volts AC 55/60hz

Watts: 55

Total Lumens: 2,724

Luminous Efficacy: 55 lm/w

LED Life Expectancy: 50,000 hours

Lighting Configuration: Flood

LED Light Color: 4000K or 5500K

Color Rendering Index: >75

Power Efficiency: 85%

Power Factor: >0.95

Amp Draw: 0.50A @ 120V, 0.25 @ 240V, 0.20 @ 277V

Housing Materials: Die Cast Aluminum Alloy 2-Part Housing

Lens Materials: Prismatic Polycarbonate Lens

Gasket Materials: Injection Molded Rubber

Ingress Protection: IP65

Ambient Temp Range: -40°C to +60°C

Mounting: Built-In Template Mount, Quick Mount

Wiring: Pigtail

Wiring Hub: Side/rear 1/2" NPT Knock-outs

Quick Summary / Features

Listed for United States and Canada

Waterproof

Operates on Standard 110-277 VAC

Vibration Resistant Construction

50,000 Hour LED Life

IP65 Waterproof

Approved for Confined Spaces

Approved for Indoor Use

Approved for Outdoor Use

Approved for Wet Locations

Ambient Temp Range -40°C to +60°

High Performance Integrated LED Assembly

Replaces 250 Watt Metal Halide Light Fixtures

Up to 79% Savings in Energy and Maintenance

Housing Matches Existing Fixtures

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The LEDVCPL-550-WCM-3480 LED Vandal Resistant Garage Light offers high light output from a compact form factor and is designed to provide a more durable and long lived alternative to halogen and metal halide units. This 55 watt LED light is designed to withstand rough abuse and tampering in public areas. They are a suitable replacement for 250 watt metal halide garage lights and produce a wide flood beam without the high heat, fragile construction, or high energy costs of traditional lighting. The LED LEDVCPL-550-WCM-3480 provides 100,000 hours of reliability and up to 79% savings compared to traditional 250 watt metal halide garage light fixtures.

The popular LEDVCPL-550-WCM-3480 vandal resistant LED garage light from Larson Electronics is designed to withstand rough abuse and tampering in high-occupancy public areas. These LEDs replace more fragile and energy consuming 250 watt metal halide fixtures, without the required maintenance or electrical requirements associated with metal halides. This 55 watt LED garage light assembly consists of an integrated LED assembly paired with a polycarbonate lens to produce a wide light distribution suitable for replacing 250 watt metal halide flood lights. This LED garage light features a 2-piece housing constructed of die cast aluminum alloy with an injected molded rubber gasket resembling that of style garage light fixtures. This LED garage light is designed to withstand demanding conditions and is IP65 waterproof and built to resist the damaging effects of an outdoor environment. This fixture can be used indoors or outdoors as well as in confined spaces without heat buildup.

The LEDVCPL-550-WCM-3480 consists of an integrated LED assembly housed within a waterproof die cast aluminum housing that is powder coated for added durability and resistance to corrosion. The built in template allows for mounting installation over standard 4" electrical boxes and easy future servicing, and the aluminum design helps heat dissipation and increased LED longevity. The LED lamp assembly is protected by a prismatic polycarbonate lens which is secured to the housing with a one piece injected rubber seal. This prismatic polycarbonate lens is designed for superior light distribution. 1/2" NPT knockouts located on the sides and back of the fixture provide a secure and sealed power connection point and rounds out this unit's weather resistant construction. The housing design of this LED garage light helps maintain building aesthetics when replacing existing garage lighting.

Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over lighting.

	<u>Metal Halide</u>	<u>LED</u>	<u>Savings</u>
Wattage	250* watts	55 watts	-130 watts
Amp Draw @ 347V AC	0.72 amps	0.15 amps	-0.57 amps
Amp Draw @ 480V AC	0.52 amps	0.11 amps	-0.41 amps
Lamp Life Expectancy	20,000 hours	100,000 hours	+80,000 hours
Operation cost per year - each (12hs/day @ 12c/kWh)	\$131.40	\$28.90	\$102.50/yr
Operation cost per year - 55 fixtures	\$6,570.00	\$1,445.00	\$5,125.00/yr

(12hs/day @ 12c/kWh)

*Includes ballast factor LED has no ballast

80% in energy savings alone, before cost of maintenance for metal halide fixtures.
Up to 79% annual savings possible by switching to LED.

This LED garage light is universal voltage, not multi-tap, and can be operated on voltages of 347 or 480 volts AC 55/60Hz providing versatile power options for all locations. The LEDVCPL-550-WCM-3480 provides an efficient and highly durable alternative to standard 250 watt metal halide as well as halogen, fluorescent, and compact fluorescent garage lights while using only a fraction of the power. With the LEDVCPL-550-WCM-3480 there is no warm up period, the light can be cycled on and off without any reduction in lamp life, there is no glass or filament to shatter or break, and the solid state LED design provides 100,000 hours of operation. The LEDVCPL-550-WCM-3480 is ideal for garage lighting, garage down lighting, monuments, docks, warehouses, large parking lots, gas stations, carports, loading areas, garages, commercial buildings, schools, public areas, and security systems just to name a few examples.

Frequently Asked Questions (FAQ)

LEDVCPL-550-WCM-3480

Product ID: 147644

Warranty: 60 Months

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDVCPL-550-WCM-3480-Color Temp-Housing Color

Example: LEDVCPL-550-WCM-3480-50K-WHT

Color Temp	
5000K	-50K
4000K	-40K

Housing Color	
WHITE	-WHT
BRONZE	-BRNZ

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)