Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-48-1L-INTL-36WT8

36W Surface Mount Explosion Proof Fluorescent Light Fixture - Paint Booth Rated - 3350 Lumens

Product ID: 147709

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-48-1L-INTL-36WT8 Explosion Proof Fluorescent Light Fixture

Dimensions: W-11.25" x L-52" x H-8.5 "
Weight: 65 Lbs
Voltage: Universal 120-277VAC 50/60 Hz
Total Watts: 18W
Total Lumens: 3,350
Lamp Life Expectancy (Hrs): 24,000 hours
Luminous Efficiency (Lm/W): 186.1 Lm/w
Color Temp: 4100K
Beam Angle: 150°
Ambient Operating Temp Range: -20°C to +70°C
Operating Temp Rating: T6 Rated
Minimum Operating Temp: -30°C
Maximum Case Temp: +90°C
Housing Material: Cast Aluminum End Caps, Aluminum Reflectors - Copper Free
Lens Material: Hardened Borosilicate Glass Tubes
Gasket Material: Buna Rubber O-Rings
Mounting: Surface Standard - Pendant Optional
Wiring Hub: 1/2" NPT

Ratings/Approvals

Class I Division 1, Groups C and D T6
Class I Division 2, Group A,B,C,D
Class II, Division 1 & 2, Groups E,F,G
NRTL Certified to UL 595 Marine Type (Saltwater)
NRTL Certified to UL 844
NRTL Certified to UL 1598 Marine Type
Listed for Paint Spray Booths
ABS Certified
California Title 24 Compliant
IP67 Rated - Waterproof
T6 Temperature Rating
NEMA 4X
Approved for Confined Spares

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Made in the USA

The Larson Electronics EPL-48-1L-INTL-36WT8 Explosion Proof Fluorescent Light Fixture is NRTL Listed for United States and Canada, and rated Class 1 Division 1 and Class 1 Division 2 for hazardous locations where flammable chemical/petrochemical vapors exist or have the potential to exist. The unit carries a T6 temperature rating and is also approved for paint spray booths.

The EPL-48-1L-INTL-36WT8 fixture is a 4 foot long lamp, Class 1 Division 1 and Class 2 Division 1 & 2 explosion proof fluorescent light which is also approved for use in paint spray booth applications. This T6 temperature rated fixture comes standard with one 18 watt T8 fluorescent bulb. The lamp is protected by a heat and impact resistant Pyrex tube and the fixture is constructed of copper free aluminum alloy. The lamp reflectors are corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture is multi-voltage capable and is available in a variety of lamp options. The EPL-48-1L-INTL-36WT8 provides operators in hazardous locations with a reliable and affordable lighting solution that provides the best explosion proof protection available without sacrificing light quality or fixture durability.

	T8	LED
Wattage	18 watts	24 watts
Amp Draw @ 120V AC	0.15 amps	0.2 amps
Amp Draw @ 277V AC	0.06 amps	0.09 amps
Amp Draw @ 12V DC	1.5 amps	2 amps
Amp Draw @ 24V DC	.75 amps	1 amp
Lamp Life Expectancy	24,000 hours	50,000 hours
Color Temperature	4100K	5300K
Operation cost per year (8hs/day @ 11c/kWh)	$5.78	$7.71

Click here to see the LED version of this fixture**Mounting Options:** Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.**Adjustable Surface Mount Brackets:** Each bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg.**Suspension Mounting:** Pendant mount fixtures hang from the ceiling and are suspended by rigid pipe. Each fixture features a 1/2" NPT junction box on one end, and a 1/2" NPT adjustable L-bracket on the other end of the fixture. Operators bring rigid pipe down to the threaded mounting hubs. Wiring is fed down through the rigid pipe to the junction box and tied in to the fixture`s lead wires, completing the electrical connection. The adjustable L-shape mounting bracket provides support for the opposite end of the fixture.**Applications:** Industrial facilities, hazardous locations, offshore refineries, marine locations, work space lighting, garage and warehouse lighting, indoor/outdoor spaces, ship yards, docks and anywhere a rugged and dependable fixture with high output and efficiency is needed.At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at

800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Over-sized, finned ballast housing for 800 mA fixtures provides more heat dissipation and extends ballast life. Larger ballast box accommodates High Output lamp ballasts. Ballast housing easily accessible and externally mounted. Top and bottom covers secured with nuts and bolts, instead of threaded through holes, which can be damaged with dirt.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the fixture, while other models require the "tap and knock off" method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.

Lamp Options


F36-T8/841 - 18 watts, 3350 lumens, 24,000 hours life, 4100 Kelvin color (Suffix -T8)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-48-1L-INTL-36WT8

Product ID: 147709

Export Control Classification Number (ECCN): EAR99

Options:

EPL-48-1L-INTL-36WT8-Mount

Example: EPL-48-1L-INTL-36WT8-SFC

Mount	
SURFACE	-SFC
PENDANT	-PND

Links (Click on the below items to view):

- MSDS (Material Safety Data Sheet
- Operations Manual
- SpecSheetFarsi
- SpecSheetFrench
- SpecSheetRussian
- SpecSheetSpanish
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map