Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-E16-4450-220V-50C

Explosion Proof Fan/Blower - 220-240VAC - 4450 CFM- 16" - C1D1 - 50' 16/3 SOOW w/ 6-20P EPP Cord Cap

Product ID: 147722

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-E16-4450-220V-50C Explosion Proof Fan/Blower
Dimensions: 19"W x 18"H x 12"D
Weight: 65 lbs
Noise Level: 90 Db
Motor: 1.5 HP, 1.1 Kw
Voltage: 220-240V AC
Horsepower: 1.5 (1.1kw)
Inrush amps (Start): 40A
Continuous Amps (Run): 8A
Fan Type: Box Fan/Blower
CFM Delivery: 4450+
Ambient Operating Temp: -20 to 180 Degrees Fahrenheit
Wiring: 50` 16/3 SOOW Cord w/ Explosion Proof Cord Cap
Cord Cap: 6-20P

UL and ATEX Approvals
Class I, Divisions 1 & 2, Group D
Class II, Divisions 1 & 2, Groups E, F and G
ATEX II 2 G EX d IIB T6
T6 Temperature Rating
Click here to see the airflow curve chart for this fan.

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The EPF-E16-4450-220V-50C from Larson Electronics is an Explosion Proof Box Fan / Blower with 15 foot static conductive duct that safely and effectively redirects stale air from hazardous location areas. This explosion proof blower meets UL and ATEX standards for hazardous locations and provides high 4450+ CFM output for effective airflow in larger spaces. The included 50` 16/3 SOOW cord with 6-20P explosion proof cord cap allows this explosion proof fan to have plenty of reach for various work areas

and job sites.
Please Note: Any free shipping offers do not apply to explosion proof fans.
This portable, electric explosion proof blower (exhaust fan) is suitable for confined spaces and is approved to UL and ATEX safety standards for hazardous locations. This fan features a high efficiency 1.5 hp motor which is fully encapsulated and a precision balanced, non sparking aluminum blower blade for high output and protection against accidental ignitions. This fan has 16 inch intake and exhaust flanges and produces over 4,450 CFM of air output for excellent movement of air in large areas.



Click Photo to Enlarge

Other features include a light weight/high strength, anti-static glass reinforced ABS housing that is corrosion proof and chemical resistant with an IP65 rated and rain tested switch enclosure. This box blower/fan operates on standard 220-240V AC with an 18 amp initial draw and 5 amp constant draw from the 1.5 horsepower motor after startup. Included with this unit is 50 feet of 16/3 SOOW cord fitted with a 6-20P explosion proof cord cap.
Note on Explosion Proof Fans: Can be used as an intake and an exhaust fan.

Click Photos to Enlarge



6-20 Straight Blade Plug

Wiring & Plug: This explosion proof flood light is equipped with 50 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. The plug is a 6-20P 20 amp straight blade plug for use with 220-240V explosion proof outlets. **PLEASE NOTE** voltage ratings on plugs and outlets are MAXIMUM voltage. For low voltage applications, proper voltage must be applied to the outlet or damage to the light fixture will occur.

Features

- 1.5 HP 1.1 kW electric motor, 115 VAC - 18 amps start and 5 amps run
- 90 dB noise level
- 16 inch intake and exhaust flange
- 4450+ cfm free air delivery (3180 CFM with 90 degree bend with 15` duct)
- Approved for Class I Group D and Class II Groups E, F, G
- Aluminum non-sparking blower blade is precision balanced

- IP65 rain tested switch enclosure
- High strength, anti-static glass reinforced ABS housing is lightweight, corrosion proof and chemical resistant
- Reversible duct adapter
- Pre-Wired With 50` 16/3 SOOW Cord and an explosion proof cord cap.

The included 15 foot long duct is a single-ply polyester reinforced PVC vinyl fabric hose design with an external wear strip reinforced with a spring steel wire helix. It is lightweight for blower applications and highly compressible. The retractability of the static conductive duct allows for convenient storage and easy transport in a fraction of its fully extended length and has low friction loss. The wear strip offers external abrasion resistance, and is listed as YL 94 V-0 flame retardant. Ambient operating temperature fro this unit ranges from -20 degrees to 180 degrees Fahrenheit.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

EPF-E16-4450-220V-50C

Product ID: 147722

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **SpecSheetSpanish**
- **STEP File (3D CAD Model)**
- **HigResPic1**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**