Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EXC-1.6-GFCI-3X-15A-1523Y

20" 12/3 SOOW Linecord with GFCI Protected Outlets - 15 Amp Max Rated - Explosion Proof Plug

Product ID: 148263

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EXC-1.6-GFCI-3X-15A-1523Y

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXC-1.6-GFCI-3X-15A-1523Y - 20" GFCI Protected Linecord w/ EXP Plug

Male Cord Cap: 5-15P - Explosion Proof
Female Receptacles: 5-15R
Voltage Rating: 120V
Max Amp Rating: 15A
Cable Type: 12/3 SOOW
Cable Length: 20"
Weight: 1.5 lbs

C1D1 15A Male Cord Cap

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EXC-1.6-GFCI-3X-15A-1523Y 20" SOOW line cord with GFCI duplex outlet is designed for heady duty and outdoor applications. This rugged extension cord is constructed of 20" 12-gauge 3-conductor wire, equipped with a 15-amp rated explosion proof 5-15 male cord cap, an inline GFCI, a 5-15R , and allows operators to provide ground fault protection within hazardous locations.

The EXC-1.6-GFCI-15A linecord provides a safe and effective way for operators to power a variety of general use devices within a hazardous location with a hot permit. 20" of chemical and abrasion resistant flexible 12/3 SOOW cord terminated in male NEMA 5-15, 15 amp rated, explosion proof cord cap. An inline GFCI and female 5-15R connector provides ground fault protection from explosion proof receptacles that do not provide GFCI protection.

Applications:
This GFCI protected linecord system is ideal for indoor or outdoor use and applications including but not limited to aircraft maintenance, alcohol processing, aerospace, chemical manufacturing, coke processing, cold storage, compressed natural gas (CNG) facilities, cranes, cryogenics, distilleries, food processing, fuel storage, gas processing plants, grain processing, laboratories, liquefied natural gas (LNG) facilities, liquid propane gas (LPG), manufacturing, marine vessels, methane production, mining, offshore, oil drilling rigs, oil refineries, paint spray booths, paper processing, petrochemical, pharmaceuticals, power plants, production refineries, sand blast cabinets, sewage and septic tanks, shipyards, solvent and cleaning areas, storage facilities, tank farms, tankers, textile, washdown areas, waste treatment plants, and woodworking. These industrial extensor cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.

Larson Electronics` Larson Electronics is a manufacturer and as such can build extension cords and portable transformer systems to your specifications. Although we carry several models of power distribution transformers, we can deliver custom ordered units almost as quickly as our prebuilt units If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs



Image: EXC-1.6-GFCI-3X-15A-1523Y

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EXC-1.6-GFCI-3X-15A-1523Y

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EXC-1.6-GFCI-3X-15A-1523Y

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EXC-1.6-GFCI-3X-15A-1523Y

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/148263.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/148263.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/148263.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/148263.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/148263.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/148263.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/148263.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/148263.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)