Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED65WRE-CPR-PTB-1227

65W LED Light with Remote Controlled Pan Tilt Base - 4355 Lumens - 120-277VAC - 3000' Spot Beam

Product ID: 148425

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LED65WRE-CPR-PTB-1227 LED Light w/ Pan/Tilt Base

Lamp Type: LED
Dimensions: 6.3"OD x 8.82"H
Total Weight: 25 lbs
Voltage: 120-277V AC, 50/60Hz
Watts: 65W
Lumens: 4,355
Luminous Efficacy: 67 Lm/W
Spot Beam: 3000`
LED Life Expectancy: 50,000 hours
Color Temperature: 6000K
Lighting Configuration: 10° Spot Beam
Amps: 0.54 @ 120V AC - 0.23 @ 277V AC
Ambient Operating Temp Range: -40°C to +85°C
Waterproof Rating: IP67
Cord Cap Options: 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist, UK BS1363, Intl. Schuko, Pigtail
Housing Material: Die Cast Aluminum
Housing Color: Black
Lens Material: Polycarbonate
Housing Color: Black
Mounting: Remote Controlled Pan/Tilt Base

Pan/Tilt Base

Ratings/Approvals

IP67 Waterproof to 1 Meter
Impact/Vibration Resistance
Shatterproof Lens
Ambient Op Temp -40°C to +85°C
Available with Choice of Plug
Ideal for Hunting and Outdoor Applications
Extremely Durable and Versatile

Dimensions: 8"L x 11"W x 10"H
Weight: 20 lbs
Rotation: 0° to 355°
Tilt: -60° to +30°
Pan Speed: 7.2°/Sec
Tilt Speed: 3.6°/Sec
Pan Electrical Power: 6 Watts
Tilt Electrical Power: 15 Watts
Maximum Load: 100 lbs
Ambient Operating Temp Range: -25°C to +50°C
Ingress Protection: IP54
Housing Material: Die-Cast Aluminum
Finish: Powder Coated - Black
Mounting: 4-Corner Thru-Hole
Remote: Hard Wired & Wireless
Wiring: 25` Cable w/ Inline Remote

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LED65WRE-CPR-PTB-1227
Product ID: 148425

Warranty: 36 Months

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
LED65WRE-CPR-PTB-1227-Cord Cap
Example: LED65WRE-CPR-PTB-1227-5.15

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UK BS1363	-BS1363
INTL. SCHUKO	-Schuko
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- **CE Certificate**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**