

### **GAU-415V-3P4W-32A-C-IP67**

**Industrial Pin and Sleeve Connector - 3P+E - 32 Amp - 380V-415V - IP67 - Hinged Cover - 60309**

**Product ID: 148579**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

#### **GAU-415V-3P4W-32A-C-IP67 Water Tight Pin and Sleeve Connector**

**Nominal Voltage:** 400V AC  
**Voltage Rating:** 380V-415V AC  
**Configuration:** 3P+E  
**Amperage:** 32  
**Reference Hour:** 6  
**Cable Gland:** PG21  
**Minimum Flexible Cable Terminal Clamping Capacity:** 2.5mm  
**Maximum Flexible Cable Terminal Clamping Capacity:** 6mm  
**Minimum Rigid Or Stranded Cable Terminal Clamping Capacity:** 2.5mm  
**Maximum Rigid Or Stranded Cable Terminal Clamping Capacity:** 10mm  
**Minimum External Cable Section:** 12.5mm  
**Maximum External Cable Section:** 19.3mm  
**Color Reference:** Red  
**Waterproof Rating:** IP67  
**Seals:** Neoprene  
**Contacts Material:** Copper Alloy  
**Housing Materials:** Toughened PVC  
**Color:** Red/Grey  
**Dimensions:** 195mm x 103mm x 95mm  
**Weight:** 3 lbs

#### **Certifications - Compliance**

IEC & EN 60309  
Portable Receptacle w/ Hinged Cover  
IP67 Rated

#### **Special Orders - Special Requirements**

Contact us for special requirements  
**Toll Free:** 1-800-369-6671  
**Fax:** 1-903-498-3364  
**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The Larson Electronics GAU-415V-3P4W-32A-C-IP67 Weatherproof Pin and Sleeve Connector is a 32 amp and 380V-415V Volts AC rated**

---

**connector approved for industrial use. This 3P+E portable receptacle is designed to provide a secure connection for electrical equipment within the general industrial environment. This pin and sleeve connector features a hinged cover and has a maximum operating voltage of 380V-415V AC. This water tight pin and sleeve connector is IP67 rated.**

This water tight 3P+E pin and sleeve portable receptacle is rated for 32 amps and 380V-415V AC. The GAU-415V-3P4W-32A-C-IP67 industrial connector features toughened PVC construction, a hinged cover, a 32 amp current rating, and a maximum voltage rating of 380V-415V AC.

**Suggested Applications:** Manufacturing, industrial, warehouse, lighting, motor-generator sets, compressors or wet areas.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---

---

## Frequently Asked Questions (FAQ)

**GAU-415V-3P4W-32A-C-IP67**

**Product ID: 148579**

**Export Control Classification Number (ECCN): EAR99**

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)