Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-HSPF-24-0.5HP-3P

24" Explosion Proof High Velocity Fan - 6500 CFM - 1/2 HP - 230/460V AC 3PH - No Cord/Power Switch

Product ID: 148788

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-HSPF-24-0.5HP-3P - 24" Explosion Proof High Velocity Fan - 6500 CFM
Type: Explosion Proof Industrial Fan
Propeller Dimensions: 24" Diameter
Propeller Material: Non-Sparking Cast Aluminum
Weight: 260 lbs
Voltage: 230/460V 60 Hz 3PH
Motor: 1/2 HP Fully Enclosed Explosion Proof
Rotations Per Minute (RPM): 1,725
Peak CFM: 6,500
Decibels @ 10`: 80
Mounting: Portable or Stationary Mount
Wiring: -
Power Switch: -
Hub: 1" NPT Hub

Quick Summary
Class I, Divisions 1 & 2, Group D
Class II, Divisions 1 & 2, Group F & G

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPF-HSPF-24-0.5HP-3P Explosion Proof Fan is a high pressure, high volume unit that can be used to support active ventilation in hazardous work locations. This robust industrial fan is capable of circulating air at a rate of 6,500 cubic feet per minute (CFM). The Class I, Group D and Class II, Group F & G rated unit is compatible with 230/460V AC three phase.

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS**

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

PRODUCT*

Features: The EPF-HSPF-24-0.5HP-3P features a non-sparking cast aluminum propeller with a 24-inch diameter. It offers compatability with 230/460V AC 60 Hz three phase. Under the hood, the machine is powered by a 1/2 HP, fully enclosed explosion proof motor. This allows the blade to rotate up to 1,725 times per minute (RPM) at a rate of 6,500 CFM. During operation, the unit emits 80 decibels from a distance of 10 feet, which is equivalent to the sound of busy city traffic. The three phase explosion proof fan weighs approximately 260 pounds and is compatible with portable and stationary mounting preferences. The high stand model features a 360-degree tilt, which offers superior flexibility during setup. This fan comes with a 1" NPT hub for completing power connections (no cord, cord cap or power switch included).

Applications: Class I, Group D and Class II, Group F & G hazardous areas that require ventilation, including (but not limited to) the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Fully enclosed explosion proof 1/2 HP motor.
2. Non-sparking cast aluminum 24" diameter propeller.
3. Class I Group D and Class II Groups F & G rated.
4. Multi-voltage capable.
5. Moves up to 6,500 cubic feet of air per minute.
6. Fully assembled and ready to install.
7.Non-tipping heavy base constructed of welded steel.
8. 1" NPT hub.
9. 360° tilt.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

EPF-HSPF-24-0.5HP-3P

Product ID: 148788

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **SpecSheetSpanish**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**