

EPF-HSPF-30-0.5HP-3P

30" Explosion Proof High Velocity Fan - 8000 CFM - 1/2 HP - 230/460V AC 3PH - No Cord/Power Switch

Product ID: 148789

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-HSPF-30-0.5HP-3P - 30" Explosion Proof High Velocity Fan - 8000 CFM

Type: Explosion Proof Industrial Fan

Propeller Dimensions: 30" Diameter

Propeller Material: Non-Sparking Cast Aluminum

Weight: 281 lbs

Voltage: 230/460V 60 Hz 3PH

Motor: 1/2 HP Fully Enclosed Explosion Proof

Rotations Per Minute (RPM): 1,725

Peak CFM: 8,000

Decibels @ 10': 86

Mounting: Portable or Stationary Mount

Wiring: -

Power Switch: -

Hub: 1" NPT Hub

Quick Summary

Class I, Divisions 1 & 2, Group D

Class II, Divisions 1 & 2, Group F & G

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPF-HSPF-30-0.5HP-3P Explosion Proof Fan is a high pressure, high volume unit that can be used to support active ventilation in hazardous work locations. This robust industrial fan is capable of circulating air at a rate of 8,000 cubic feet per minute (CFM). The Class I, Group D and Class II, Group F & G rated unit is compatible with 230/460V AC three phase.

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS**

PRODUCT*

Features: The EPF-HSPF-30-0.5HP-3P features a non-sparking cast aluminum propeller with a 30-inch diameter. It offers compatability with 230/460V AC 60 Hz three phase. Under the hood, the machine is powered by a 1/2 HP, fully enclosed explosion proof motor. This allows the blade to rotate up to 1,725 times per minute (RPM) at a rate of 8,000 CFM. During operation, the unit emits 86 decibels from a distance of 10 feet, which is equivalent to the sound of busy city traffic. The three phase explosion proof fan weighs approximately 281 pounds and is compatible with portable and stationary mounting preferences. The high stand model features a 360-degree tilt, which offers superior flexibility during setup. This fan comes with a 1" NPT hub for completing power connections (no cord, cord cap and power switch).

Applications: Class I, Group D and Class II, Group F & G hazardous areas that require ventilation, including (but not limited to) the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Fully enclosed explosion proof 1/2 HP motor.
2. Non-sparking cast aluminum 30" diameter propeller.
3. Class I Group D and Class II Groups F & G rated.
4. Multi-voltage capable.
5. Moves up to 8,000 cubic feet of air per minute.
6. Fully assembled and ready to install.
7. Non-tipping heavy base constructed of welded steel.
8. 1" NPT hub.
9. 360° tilt.

Frequently Asked Questions (FAQ)

EPF-HSPF-30-0.5HP-3P

Product ID: 148789

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)