Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ARTL-BLD-RND-TF-5L-T3

15W Round Flat Top LED Bollard Light - 1,022 Lumens - 120/277V AC - Wet Location Approved

Product ID: 148817

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ARTL-BLD-RND-TF-5L-T3 Round Flat Top LED Bollard
Lamp Type: LED
Dimensions: 41 5/8"-H x 7"-Diameter
Weight: -
Voltage: 120-277V AC @ 50/60 Hz
Total Watts: 15W
Lumens: 2,089 (Nominal) 1,022 (Delivered) @ 5000K
Luminous Efficacy: 68.13 Lm/W @ 5000k
Life Expectancy: 50,000+ hours
Light Color: Cool White
Color Temperature: 3000K, 4000K and 5000K
Beam Angle: Type III
Color Rendering Index: 83 CRI
Operating Temp Range: -40ºC to +40ºC
Housing Material: Extruded Aluminum
Finish: Powder Coated Over Chromate Conversion Coating
Housing Color: Bronze, Black or White
Lens Material: Clear Polycarbonate
Mount: Flush Surface Mounting With 8" Anchor Bolts

Ratings/Approvals
Listed for United States & Canada
Approved for Wet Locations
Electronic Driver
Round Flat Top Bollard

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The ATRL-BLD-RND-TF-5L-T3 is a round flat top LED bollard, suitable to illuminate outdoor walkways, steps, pathways and parking lots, as well as provide physical protection from and visible barriers for vehicles. This IP65 rated round bollard has a standard 5,000K color temperature with a

clear polycarbonate lens that delivers 1,022 lumens in a Type III distribution. This aluminum vandal-resistant housed bollard features an electronic driver, which runs on 120-277V AC @ 50/60 Hz. This bollard is listed for United States and Canada and approved for wet locations.

The ATRL-BLD-RND-TF-5L-T3 produces 15 watts of Type III light distribution, which projects light forward and outward to fill an area, making this bollard ideal for parking lots, landscape illumination and other areas where perimeter lighting is necessary. This durable LED bollard operates on 120-277V AC @ 50/60 Hz with color temperatures of 3,000K, 4,000K and 5,000K. The LED bulbs have a rated life span of 50,000 hours and a CRI of 83. For maximum control the bollard LED array includes an electronic driver, which is located in a sealed internal driver tray for security and easy maintenance.

This durable flat top bollard features flat top housing constructed of extruded aluminum with a powder coating available in bronze, black, or white finishes, over a corrosion-resistant chromate conversion coating. The bollard has a flush mounting base and includes a mounting kit with 8” anchor bolts, which are drilled into the ground to secure the bollard down and provide vandal-resistance. It is IP65 rated, resistant to dust and protected against the corrosive effects of water jet wash-downs. The ATRL-BLD-RND-TF-5L-T3 can operate in temperatures -40ºC to +40ºC.

Type III Distribution: Type III light distribution projects light forward and outward at a preferred lateral width of 40 degrees. Type III distribution is ideal for roadway lighting and general landscape perimeter applications such as retail centers, office buildings and airport parking lots. Type III fixtures should be mounted on the sides, or around the perimeter of the space requiring illumination.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Mounting: The ATRL-BLD-RND-TF-5L-T3 includes a mounting kit with 8? vandal-resistant anchor bolts.

Applications: Walkways, buildings, perimeter lighting, commercial lighting, post lighting, directional lighting, outdoor illumination, upgrading (from CFLs to LEDs), background lighting, general area lighting, residential lighting, landscape lighting and more.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ARTL-BLD-RND-TF-5L-T3

Product ID: 148817

Harmonized System (HS) Code: 9405.10.8020

Export Control Classification Number (ECCN): EAR99

Options:

ARTL-BLD-RND-TF-5L-T3-Color-Color Temp

Example: ARTL-BLD-RND-TF-5L-T3-BRZ-30K

Color	
BRONZE	-BRZ
BLACK	-BLK
WHITE	-WHT

Color Temp	
3000K	-30K
4000K	-40K
5000K	-50K

Links (Click on the below items to view):

- **Operations Manual**
- **SpecSheetRussian**
- **SpecSheetSpanish**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**