Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ATEX-HALP-48-2L-T8-2X18W

36W Explosion Proof Fluorescent Fixture - (2) 4' 18W Lamps - 220/240V AC - ATEX/IECEx

Product ID: 148927

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-HALP-48-2L-T8-2X18W Hazardous Location Lamp

Lamp Type: Fluorescent

Dimensions: 62.4" x 7.2" x 4.9"

Weight: 14.9 lbs

Voltage: 220-240V AC 50/60 Hz

DC Voltage: 198-264V DC (Switching On), 176-264V DC (Operation)

Total Watts: 36W (18W per Lamp)

Lamp Life Expectancy: 24,000 Hours

Beam Angle: Flood

Ambient Operating Temp Range:-30°C to +50°C

Operating Temp Range: T4 Rated

Housing Material: Polyester and Glass Fiber Housing

Gasket Material: Silicone

Lens Material: Polycarbonate

Mounting: Ceiling or Wall

Wiring Hub: (2) M25 Hubs on Side

Ratings/Approvals

IECEx PTB 13.0003

Ex d e IIC T4 Gb or Ex db eb IIC T4

Ex tb IIIC T80°C Db or Ex tb IIIC T80°C

PTB 13 ATEX 2004

Ex II 2 G Ex d e IIC T4 Gb or Ex db eb IIC T4

E II 2 D Ex tb IIIC T80°C Db or Ex tb IIIC T80°C

Central Locking

IP66

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The ATEX-HALP-48-2L-T8-2X18W Explosion Proof Fluorescent Fixture from Larson Electronics is ATEX/IECEx approved for Zones 1 and 2 and 21 and 22. This 36-watt unit is equipped with two, 4-foot lamps that operate on 220-240V AC. The IP66-rated fixture is made out of non-sparking

materials that are highly resistant to rough impacts (IK10). This fluorescent lamp can be mounted on ceilings or walls using a pair of stainless steel mounting brackets.

The ATEX-HALP-48-2L-T8-2X18W is designed for use in hazardous locations and flammable buildings that require ATEX/IECEx rated fixtures. Consisting of two, 4-foot fluorescent lamps, the cold start unit is compatible with 220-240V AC, while consuming 36 watts (18 watts per lamp) during operation. A flood beam configuration ensures full coverage of the location when the light is in use. The lamp carries a T4 temperature rating. A NC switch provides all-pole disconnection when the unit is opened.

This ATEX-rated fluorescent fixture is constructed of non-sparking materials for protection in flammable work sites. The housing on the unit is made out of glass fiber-reinforced polyester resin with polycarbonate lens and silicon foam gaskets. The IP66 unit offers exceptional resistance to hard impacts (IK10), with a threshold of 20 joules. Operators can lock the lamp using a small socket key (M8/wrench size 13).

Mounting: The ATEX-HALP-48-2L-T8-2X18W is compatible with wall or ceiling mount installations. Each fixture is equipped with two M25 hubs on either side of the lamp for completing electrial connections. When a stainless steel mounting bracket is attached to the luminary for mounting, it can be swiveled in increments of 15 degrees for accurate targeting.

Suggested Applications: Petrochemical facilities, lubrication pits, oil drilling rigs, crew quarters, solvent/cleaning areas, water treatment areas, processing plants, marine loading docks, shipyards, ports and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

ATEX-HALP-48-2L-T8-2X18W

Product ID: 148927

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **SpecSheetFrench**
- **SpecSheetSpanish**
- **STEP File (3D CAD Model)**
- **HigResPic1**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**