

LLP-MCC-TR-MTX-125-V1

LED Light Package for McCormick MTX125 Tractor - (6) LEDEQ-3X3-CPR & (2) IL-LED-DLR-5X2

Product ID: 149084

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

[LLP-MCC-TR-MTX-125-V1 LED Tractor Light Package](#)
[LEDEQ-3X3-CPR LED Work Light Bar](#)

[Quick Summary](#)

Buy American Compliant

The LLP-MCC-TR-MTX-125-V1 LED Tractor Light Package comes with 6 [LEDEQ-3X3-CPR](#) LED Work Lights. Two of these lights come in a spot beam configuration for use as rear fender lights and the other four come in a flood beam configuration. Two for use as rear back cab flood lights and two for use as top front cab lights. The LLP-MCC-TR-MTX-125-V1 also includes 2 [IL-LED-DLR-5X2](#) 5" x 2" Rectangular LED Lights to use as grill lights. The LLP-MCC-TR-MTX-125-V1 LED Light Package is ideal for installation and use on a McCormick International MTX125 Tractor. Each LEDEQ-3X2-CPR produces 2,100 lumens, each LEDEQ-3X3-CPR produces 2,975 lumens and each IL-LED-DLR-5X2 produces 1,440 lumens of high-intensity LED light output with low voltage and amp draw, a 50,000 hour rated service life and 9 to 42 volt compatibility that provides operators with a versatile and powerful LED tractor lighting solution.

LEDEQ-3X3-CPR: This LED light bar is capable of emitting up to 2,975 lumens during operation. The 45-watt fixture features 9V-64V DC input voltages and an electric current of 2.8 A. During output, the luminary shines a brilliant white light with a color temperature rating of 6,000-6,500K. The fixture is capable of withstanding rough treatment and immersions up to 3.3 feet (IP67 with air-

breather design).

The LEDEQ-3X3-CPR light's housing is made up of aluminum, while the lens is constructed of polycarbonate. This unit complies with CE, ROHS and E4 standards. It is IP67 certified, which provides complete protection from dust and water immersions up to 3.3 feet. This lamp uses Cree® LED units that have been chosen for their high lumen per watt ratio and extreme longevity. These Cree® LEDs generate a high lumens-per-watt ratio, effective lumen output and supports 70 percent lumen retention at 50,000 hours, giving them better efficiency and operational life than traditional light sources.

LEDEQ-3X3-CPR Mounting: It is mounted using a U-bracket style trunnion mount, making vertical light direction adjustments easy to implement.

IL-LED-DLR-5X2: This low voltage, 30-watt luminary emits a bright white light with a color temperature rating of 6,000K. The LED unit is waterproof, offering protection from rain and wetness in outdoor environments. The IL-LED-DLR-5X2 is a suitable replacement for external tractor lighting systems. This 30-watt LED light operates on 12-24V DC. When in use, the luminary emits 1,440 lumens of white light with a color temperature rating of 6,000K in a flood beam configuration. The unit is constructed of sturdy aluminum and features waterproof protection. The back of the IL-LED-DLR-5X2 supports a breathable design for robust air flow, along with a standard 2-pin connector for quick installation.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Mounting: The LED lights in this cab light upgrade kit mount in existing lamp holders for halogen lamps on McCormick International MTX125 tractors. This means that this LED cab light upgrade kit is easy to install without any major modifications to the cab or body of the tractor.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)







LLP-MCC-TR-MTX-125-V1

Product ID: 149084

Harmonized System (HS) Code: 8512.20.2080

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)