

WAL-TPM-250LTL-LED-25C

240W Pole Mount LED Flood Light Tower - 7-12' Pole - 25' 16/3 SOOW w/ General Area Cord Cap

Product ID: 149140

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

WAL-TPM-250LTL-LED-25C Pole Mount LED Flood Light Tower

Lamp Type: CREE® LED

Dimensions: Light Head: 22.92"L x 14.51"W x 5.153"D - 7-12' Tower

Weight: 50 lbs

Total Watts: 240

Total Lumens: 32,400

Luminous Efficiency: 135 lm/w

Beam Configurations: 10° Spot, 24° Wide Spot, 38° Narrow Flood, 60° Flood, or 90° Wide Flood

LED Color Temperature: 5000K or 4000K

LED Life Expectancy: 80,000 hours

Optics Efficiency: 98% - PMMA High Transmittance Optics

Led Drive %: 90%

Voltage: 120-277V AC

Amp Draw: 2.08A @ 120V, 0.625A @ 240V, 0.54A @ 277V

Wiring: 25' 16/3 SOOW Cable w/ General Area Cord Cap

Cord Cap Options: 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist, UK BS1363, Intl. Schuko, Pigtail

Mounting: Pole Mount Aluminum Tower - 7-12' Adjustable

Materials: Die Cast Aluminum Housing, PMMA Optics

Housing Color: Natural Aluminum

Ambient Temperature Range: -40°C to +80°C

Waterproof Rating: IP67

Quick Summary

550 Watt Metal Halide Replacement

Ambient Op Temp -40°C to +80°C

7-12' Adjustable Aluminum Tower

98% Transmission High Purity PMMA Optics

Multiple LED Banks for Heat Dispersion

135 Lumens Per Watt Efficiency

70% Lumen Retention after 80,000 Hours

UL1012 Compliant

UL60950-1 Compliant

CE Certified

RoHS Compliant

IP67 Rated Waterproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)





WAL-TPM-250LTL-LED-25C

Product ID: 149140

Warranty: 60 Months

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

WAL-TPM-250LTL-LED-25C-Light Config-Cord Cap

Example: WAL-TPM-250LTL-LED-25C-10SP-5.15

Light Config	
10° SPOT	-10SP
24° WIDE SPOT	-24WS
38° NARROW FLOOD	-38NF
60° FLOOD	-60F
90° WIDE FLOOD	-90WF

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UK BS1363	-BS1363
INTL. SCHUKO	-Schuko
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)