

EXPCMR-IP-POE-DPTZ-SFC

6MP Explosion Proof Digital Pan Tilt Zoom Security Camera - 360° - PTZ- C1D1 - Surface Mount Bracket

Product ID: 149263

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-IP-POE-DPTZ-SFC Explosion Proof Digital PTZ

Unit Type: Explosion Proof Camera

Dimensions: 9.13"L x 15.63"W x 7.18"H

Total Watts: 12W Max

Voltage: 12V DC

PoE: 802.3af

Image Sensor: Progressive Scan CMOS

Camera Resolution: 3072 x 2048

Megapixel: 6

Compression Type: H.264, MJPEG

Frame Rate: High-frame Mode- 1 Fisheye 25fps @ 2048 x 1536, 30fps @ 2048 x 2048, 4x ePTZ 30fps @ 1024 x 768; Multi-channel Mode- 1 x Fisheye 15fps @ 1280 x 1280, 1x Panoramic 15fps @ 2048 x 1536, 3x ePTZ 15fps @ 1024 x 768

Day/Night Function: True D/N w/Mechanical Cut Filter

IR Wavelength/Range: 850 nm/49 Feet

Relative Aperture (F-stop): 2.8

FOV (Degrees): 360°

Audio Compression: 64Kbps (G.711)/16Kbps (G.726)/MP2L2

Audio Streaming: Two-way Audio Streaming w/ Built-in Mic

Ethernet Interface: RJ-45

Ethernet Ports/Speed: 1, 10/100

Networking Protocols: TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP

Recording: Email Notification, Event Log, Event Notification, Event Search, Motion Detection, Pre/Post Alarm Recording, Privacy Video Block, Video Analytics Capable

Storage Capacity: 64 GB max via SD card slot

Connectors: Sensor Inputs (1), Alarm Output (1), Audio In (1), Audio Out (1)

Quick Summary

Class I, Div. 1 & 2, Groups B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Div. 1 & 2, Groups E, F, G

Class III, Div. 1 & 2

NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

ATEX/IEC Ex

Ex d IIC T6 or T5

Motion Detection

Day/Night Operation

Ambient Temperature Range: -22°F ~ 140°F

Material: Copper-free Aluminum

Finish: Electrostatically Applied Powder Epoxy/Polyester Finish

Lens Cover Material: Tempered Soda Lime Glass

Wiring Hub: (2) 3/4" - 14 NPT Drilled and Tapped Conduit Openings

Mount: Flat Surface/Trunnion Mount

Camera Weight: 13.1 lbs

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EXPCMR-IP-POE-DPTZ-SFC from Larson Electronics is an Explosion Proof Digital Pan Tilt Zoom Camera that is designed for security and remote observation in both indoor and outdoor hazardous environments. This high resolution day/night camera features a mechanical infrared cut filter, motion detection and up to 64GB internal storage. The security device comes with the following explosion proof ratings: Class I, Div. 1 & 2, Groups B, C, D; Class I, Zone 1 and Class II, Div. 1 & 2, Groups E, F, G. Constructed of heavy duty aluminum, the unit supports 360° fisheye panoramic surround views and up to five independent camera views at once on-screen.

Camera Features: The EXPCMR-IP-POE-DPTZ-SFC digital PTZ camera provides operators in hazardous areas with crisp high resolution images. Equipped with a 1.27 mm optical lens, this 12W unit produces up to 6.0 megapixel (3072 x 2048) resolution while operating at 12V DC. Operators may choose from the following viewing modes: fisheye, horizontal panoramic and ePTZ quad view. A 360° fisheye panoramic surround view offers wider coverage and eliminates blind spots, while a 180° panoramic view provides end-to-end horizontal coverage. For operation in dark hazardous locations, Infrared (IR) LEDs may be enabled for coverage up to 49 feet. Smart IR technology reduces over-exposure of the IR LEDs at the center of the image.

This device features two-way audio using a built-in speaker and microphone. The EXPCMR-IP-POE-DPTZ-SFC security camera is designed to perform under harsh and rugged conditions. For use in extreme environments, the IP66 rated waterproof unit resists the corrosive effects of weather, dust, dirt, and humidity. With a copper-free aluminum housing, the camera is capable of operating in hazardous locations with temperatures ranging between -22°F and 140°F, as well as 0% to 95% non-condensing, humid environments.

Wiring: This unit is designed to operate on 12V DC, consuming a maximum of 12W per system. Two 3/4" - 14 NPT drilled and tapped conduit openings (one top and one bottom) are available for wiring.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 - 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 - 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Mounting: The EXPCMR-IP-POE-DPTZ-SFC explosion proof security camera can be mounted on flat surfaces via an adjustable trunnion mount.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, offshore and land based rigs, indoor and outdoor security, commercial buildings, service garages, oil refineries and other applicable hazardous locations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to

honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)









EXPCMR-IP-POE-DPTZ-SFC

Product ID: 149263

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [Operations Manual](#)
- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [Video1](#)
- [Video2](#)
- [Video3](#)
- [Video4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)