Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-HB-1000W-LED-SS-480V

1000W High Intensity LED Crane Light - 110,000 Lumens - 347-480V AC - Stainless Steel Bracket

Product ID: 149533

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-HB-1000W-LED-SS-480V LED Crane Light

Lamp Type: Cree® XTE LEDs
Dimensions: 17.17" H x 21.02"W x 19.57"D (23.68"D w/ Mounting Bracket)
Weight: 66.25 Lbs
Total Watts: 1000 Watts
Total Lumens: 110,000
LED Chip: CREE XPE
LED Qty: 440
Luminous Efficiency: 110 Lm/W
Beam Configurations: 10° Spot or 60° Flood
LED Color Temperature: Cool White - 5500K
LED Life Expectancy: 50,000 hours
Led Drive %: 90%
Voltage: 347-480V AC
Amp Draw: 3.00A @ 347V, 2.17A @ 480V
Wiring: 10` Pigtail w/ Flying Leads
Mounting: Stainless Steel Flat Surface Trunnion Mount U-Bracket w/ 240° Adjustability
Materials: Die Cast Aluminum Housing, High Specular Reflector
Housing Color: Powder Coated Black
Ambient Temperature Range: -40°C to +80°C
Waterproof Rating: IP65
Application: Crane Lighting - Ideal for Mounting at 50+ Foot Heights

Quick Summary

2500 Watt Metal Halide Replacement
Ambient Op Temp -40°C to +80°C
Ideal for Crane Lighting
High Specular Reflectors
110 Lumens Per Watt Efficiency
IP65 Rated Waterproof
RoHS Compliant
70% Lumen Retention after 50,000 Hours
UL1012 Compliant
UL60950-1 Compliant
CE Certified

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The GAU-HB-1000W-LED-SS-480V from Larson Electronics is an LED

Crane Light that offers intense light output and is ideal for mounting to indoor or outdoor cranes at mounting heights of 50 feet and higher. Producing 110,000 lumens, a 3.00 amp draw at 347V, 50,000 hour service life, 347-480V volt compatibility, and IP65 waterproof rating, this LED crane light provides operators with a rugged and powerful LED alternative to 2500 watt metal halide lamps that uses little power and can withstand rugged use and abusive conditions. The GAU-HB-1000W-LED-SS-480V features a stainless steel bracket for secure crane mounting with high corrosion resistance.

The GAU-HB-1000W-LED-SS-480V LED light from Larson Electronics produces 110,000 lumens of high intensity light while drawing only 1,000 watts at 3.00 amps from a 347 volt electrical system. High output Cree® XTE LEDs are paired with a high purity polished aluminum reflector to produce a well focused 10° spot beam that is ideal for providing far reaching concentrated illumination. We also offer optional reflector a 60° flood beam spreads for covering wide areas. The spot beams are tightly focused and are designed for high elevation mounting to achieve distance, making spot versions ideal for high mast and spots lighting. The flood beams are designed to provide more light over a larger area nearer the fixture, making flood versions ideal for use as dedicated work and area lights.

GAU-HB-1000W-LED-SS-480V lights are ideal replacements for fragile and hot running 2500 watt metal halide lamps. They offer low power requirements, high durability and a versatile mounting system that makes these LED light emitters a superior lighting solution for demanding applications where power and reliability is critical. The heavy duty design and high power of these LED lights also makes them suitable for a wide array of applications including but not limited to: crane lighting at 50+ foot heights.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units features a cast aluminum heat sink with copper heatpipes behind the reflector assembly to control heat buildup along with gear-slotting fin technology to dissipate heat. This heat sink is designed to allow ample air flow through the fixture, cooling the unit during operation. This allows for more thorough cooling of the LEDs for extended operating periods and allows the LEDs to be driven at up to 90% capacity without overheating or visible loss of light output. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Durability: As well as unparalleled heat control, the GAU-HB-1000W-LED-SS-480V series of LED lights from Larson Electronics also offer IP65 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can withstand rapid temperature changes of -40° Celsius to +50° Celsius, are waterproof, and resist ingress of dust, dirt and humidity. The housings are formed from die cast aluminum lens is constructed of impact and shatter resistant polycarbonate. The Cree® XTE LEDs help these units achieve resistance to vibrations and are rated at 70% lumen maintenance after 50,000 hours of use. We recommend these LED lights for use in applications

where a lot of vibration, dust, dirt, dampness and abusive working conditions are encountered.

Voltage: This light is universal voltage capable and can be operated with 347-480V AC without modifications. 347V is common in Western Canada, while 480V is common in the United States and Eastern Canada. The drivers in this unit provide the ability to automatically monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These lights can operate on current ranging from 347V to 480V 50/60Hz without any modifications necessary as a result. This ability to sense and adjust input current also provides protection against voltage spikes and drops that can occur in electrical systems which would otherwise result in burning up or premature LED failure without it.

Mounting: Each unit is equipped with a stainless steel back mount trunnion style mounting bracket that allows the light to be attached to flat surfaces and adjusted through 240° of vertical movement. To adjust the unit after mounting, the user simply loosens the set screws located on either side of the unit, moves it into the desired position, then re-tightens the screws. The base of the mounting trunnion is equipped with several machined slots which allow users to utilize existing mounting holes and slide the unit for precise mount positioning.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)






IP65

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-HB-1000W-LED-SS-480V

Product ID: 149533

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GAU-HB-1000W-LED-SS-480V-Beam Angle

Example: GAU-HB-1000W-LED-SS-480V-10SP

Beam Angle	
10° SPOT	-10SP
60° FLOOD	-60F

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**