Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 149620

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXHL-TP-RPS-17AH-LE1 Explosion Proof LED Light Fixture

Lamp Type: LED
Dimensions: 8"L x 6"W x 14"H - Lamp
Weight: -
Voltage: Rechargeable/Battery Powered Unit
Watts: 12W
Lumens: 1,320
Luminous Efficacy: 110 Lm/W
LED Light Color: 6000K - White
LED Life Expectancy: 50,000 hours
Lighting Configuration: 10° Spot or 40° Flood
Spot Beam: 800`L x 140`W
Flood Beam: 300`L x 225`W
Ambient Operating Temp Range: -40°C to +60°C
Housing Material: Aluminum
Lens Material: Polycarbonate
Mounting: 3.5` to 10` Aluminum Tripod
Battery Runtime: 1.5 Hrs
Charger: AC Charger w/ Connector

Ratings/Approvals

Listed for United States, Canada, Europe, Asia
Class I, Div. 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Div. 1 & 2, Groups E, F ,G
Class III, Div. 1 & 2
NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)
ATEX Ex II 2 G / D
IECEx db IIC Gb
IECEx tb IIC Db IP66
Rechargeable LED Light

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in Texas

The EXHL-TP-RPS-17AH-LE1 from Larson Electronics is a Tripod-mounted Rechargeable Explosion Proof LED Light Tower offers a portable and convenient source of high-intensity LED light. This rechargeable LED produces 1,320 lumens while drawing only 12 watts. The EXHL-TP-RPS-17AH-LE1 is Class I, Divisions 1 & 2, Groups B, C, D, Class I, Zones 1 & 2, Groups IIB+H2, IIA, Class II, Divisions 1 & 2, Groups E, F ,G and Class III Divisions 1 & 2 rated for hazardous areas and is listed for use worldwide including the United States, Canada, Europe and Asia. This battery-powered LED light fixture provides up to 1.5 hours of use and superior illumination in hazardous work sites.

The EXHL-TP-RPS-17AH-LE1 produces 1,320 lumens of high-intensity LED light for illumination within hazardous areas and potentially explosive work environments. This explosion proof LED light fixture is battery powered and rechargeable, offering a runtime of 1.5 hours in a fully charged state. The EXHL-TP-RPS-17AH-LE1 is available in two lighting configurations; spot and flood. The spot configuration features a 10° beam that measures 800`L and 140` W. The flood configuration throws a 40° beam that measures 300`L and 225`W. This portable unit features an aluminum tripod mount and is designed for hand-held applications, capable of either being carried, like a compact lantern, or used hands-free, as a standalone light.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED`s core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Durability: The EXHL-TP-RPS-17AH-LE1 explosion proof LED light fixture from Larson Electronics is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining lightweight and easy to use. These units can operate in temperatures of -40° Celsius to 60° Celsius, are waterproof to 3 meters and resist the ingress of dust, dirt and humidity. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations.

Battery: This unit is powered by a rechargeable battery. In a fully charged state, the power cell offers 1.5 hours of runtime. Operators can charge the battery using an AC charger (with an appropriate connector) that plugs into mainstream power outside of the hazardous area. A heavy-duty SOOW cord connects the bottom and top enclosure and facilitates electrical connections.

Mounting: This explosion proof LED light tower comes equipped with an adjustable aluminum tripod that can reach heights up to 10 feet and can be lowered to 3.5 feet for applications where a lower height is required or for storage and transportation. The heavy duty aluminum tripod is durable and lightweight, making it perfect for on the go applications requiring bright illumination.

High Quality Features	Superior LED Benefits
	1. 50,000+ hour lifespan. 2. Can SAVE 50% or more on energy. 3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
1. Low power consumption. 2. Instant on/off operation. 3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy. 4. Superior color rendering compared to HPS, LPS, MH. 5. Retains 70% lumen output after 50,000 operating hours. 6. Powder coated aluminum fixture body. 7. Portable A-frame w/ adjustable U-bracket mount. 8. Low profile - Light weight 9. 1,320 Lumen output from 12 watts	4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration) 5. 100% recyclable. 6. No toxins-lead, mercury. 7. No UV light, infrared radiation or CO2 emissions. 8. Qualifies buildings for LED and other sustainable business certifications. 9. Bright, even light maintains consistent color over time. 10. Instant on/off - No flickering, delays or buzzing. 11. Very good color rendering. 12. Vibration/impact resistant. 13. Significantly cooler operation. 14. Less frequent outages, higher output improves workplace safety.

Applications: Hazardous locations, inspections, detailed tasks, petroleum refineries, chemical and petrochemical plants, paint spray booths, food manufacturing buildings, grain storage sites, woodshops, automotive garages and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide

replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 149620

Export Control Classification Number (ECCN): EAR99

Options:

-Voltage-Beam Config
Example: -120V-SP

Voltage	
120V	-120V
240V	-240V

Beam Config	
SPOT	-SP
FLOOD	-FL

Links (Click on the below items to view):

- **SpecSheetSpanish**(https://www.larsonelectronics.com//images/product/SpecSheetSpanish/149620.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/149620.JPG)
- **Video1**(https://www.youtube.com/watch?v=OGbw09xDTqI)
- **Video2**(https://www.youtube.com/watch?v=ZEWSEBXdzYE)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)