

HLSW-SS-SW20-3PSW-LCK-SRMM

Explosion Proof Stainless Steel Maintained 3-Position Key Selector Switch - Spring Return - Mom. Rig

Product ID: 149865

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLSW-SS-SW20-3PSW-LCK-SRMM Stainless Steel Maintained Keyed Selector Switch

Type: Maintained Contact 3-Position Selector Switch

Dimensions: 3.95"W x 4.21"H x 4.16"D

Voltage Rating: 690V AC, 20A, 50-60Hz

Horsepower Rating: 2 HP

Ambient Operating Temp Range: -50°C to +60°C

UV Protection: f1

Housing Materials: Stainless Steel Glass Reinforced Impact Resistant Antistatic Material

Housing Color: Black

Switch Color: Black

Legend Plate Color: -

Legend Plate Labels: -

Contact Blocks: (2) Normally Open

Flame Retardant Rating: V-0

Gasket Material: Silicone

Mounting: Din Rail Mount

Wiring Hub: (1) 3/4" NPT SS Hub

Ratings/Approvals

Class I, Division 2, Groups A, B, C, D

Class I, Zone 1, AEx de IIC T4/T5/T6 Gb

Class II, Division 2, Groups E, F, G

Class III

Type 3, 4, 4X, 12, 13

II 2 G Ex de IIC T4/T5/T6 Gb

II 2 D Ex tb IIIC T4/T5/T6 Db IP66

NEMA 3, 4, 4X, 12, 13

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The HLSW-SS-SW20-3PSW-LCK-SRMM from Larson Electronics is a stainless steel maintained 3-position keyed contact switch that is rated

for Class I Division 2 Groups A, B, C & D, Class II, Division 2, Groups E, F & G and Class III hazardous environments. This ATEX certified 3-position keyed selector switch has a din rail mount design and is constructed of an impact resistant glass reinforced stainless steel material with silicone gaskets. The HLSW-SS-SW20-3PSW-LCK-SRMM has a black housing color with a black two-way switch and boasts a compact size for convenient mounting and use.

This Class I Division 2 Groups A, B, C & D rated stainless steel maintained contact switch is designed for din rail mounting. It is ideal for mounting and use in petroleum refineries, chemical plants, petrochemical plants and other facilities where similar conditions exist. The HLSW-SS-SW20-3PSW-LCK-SRMM has explosion protected contact blocks that are rated for voltages up to 690V AC, is capable of handling 20 amps for switching duty and has a horsepower rating of 2 HP. This 3-position keyed selector switch also features silver alloy contacts with gold flashing. This stainless steel maintained contact switch has an ambient operating temperature of -50°C to +60°C and can be used in conjunction with motor starters or contactors for remote operation of motors.

The HLSW-SS-SW20-3PSW-LCK-SRMM C1D2 stainless steel 3-position keyed selector switch with a momentary spring return to the right and maintained in the center and to the left. This selector switch features a stainless steel housing that is constructed of a PA6 glass reinforced antistatic material that is impact resistant, f1 UV resistant and has a flame retardant rating of V-0. The housing on this switch is black and the switch itself is also black. This switch has a 3/4" NPT SS hub and features silicone gasketing throughout. The HLSW-SS-SW20-3PSW-LCK-SRMM has two normally open contact blocks. Normally open is a contact that does not flow current in its normal state. In the case of this switch, the normally open contact would be labeled as "OFF" because the circuit is "open" or not allowing current to flow.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

HLSW-SS-SW20-3PSW-LCK-SRMM

Product ID: 149865

Warranty: 12 Months

Export Control Classification Number (ECCN): EAR99

Options:

HLSW-SS-SW20-3PSW-LCK-SRMM-Termination

Example: HLSW-SS-SW20-3PSW-LCK-SRMM-DE

Termination	
DEAD END	-DE
FEED THRU	-FT

Links (Click on the below items to view):

- [ATEX Certificate \(European Explosion Proof\)](#)
- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [IEC Ex Certificate \(International Explosion Proof\)](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)