

28W Explosion Proof Two Lamp LED Fixture - C1D1&2 - C2D1&2 - 50' 16/3 SOOW Cord w/ EYS Sealoff

[EPL-24-2L-LED-EYS-50C-EPP](#)



EPL-24-2L-LED-EYS-50C-EPP Explosion Proof LED Light w/ EYS Sealoff

NRTL Listed for United States & Canada

Dimensions: 11.25"W x 27.5"L x 8.5"H

Weight: 32 Lbs

Voltage: Universal 120-277VAC 50/60 Hz

Total Watts: 28 Watts

Total Lumens: 3,500

LED Lamp Life Expectancy: 50,000+ Hours

Luminous Efficiency: 125 Lm/W

Color Temp: 5600K, 4500K or 3000K

Color Rendering Index: >80

Beam Angle: 150°

Power Efficiency: 90%

Power Factor: >0.95

Ambient Operating Temp Range: -30°C to +85°C

Operating Temp Rating: T6 Rated

Minimum Operating Temp: -30°C

Maximum Case Temp: +90°C

Housing Material: Cast Aluminum End Caps, Aluminum Reflectors - Copper Free

Lens Material: Hardened Borosilicate Glass Tubes

Gasket Material: Buna Rubber O-Rings

Mounting: Surface Standard - Pendant Optional

Wiring: EYS Sealoff - 50' 16/3 SOOW Cord w/ Explosion Proof Cord Cap

Cord Cap Options: 5-15P, 5-20P or 6-20P

Ratings/Approvals

Class I Division 1 Groups C & D

Class I Division 2 Groups A, B, C & D

Class II Divisions 1 & 2, Groups E, F & G

NRTL Certified to UL 595 Marine Type (Saltwater)

NRTL Certified to UL 844

NRTL Certified to UL 1598 Marine Type

Certified Canadian Standards

Listed for Paint Spray Booths

California Title 24 Compliant

IP67 Rated - Waterproof

T6 Temperature Rating

NEMA 4X

LEL Listed LED Lamps

Approved for Confined Spaces

Silicone Free

Factory Sealed Fixture

Made in the USA

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-498-3363

E-mail: sales@larsonelectronics.com



Options:

EPL-24-2L-LED-EYS-50C-EPP-Mounting-Cord Cap-Color Temp

Example: EPL-24-2L-LED-EYS-50C-EPP-SFC-SFC-56K

Mounting	
SURFACE	-SFC
PENDANT	-PND

Cord Cap	
5-15P	-SFC
5-20P	-PND

Color Temp	
5600K	-56K
4500K	-45K
3500K	-35K

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)