

18" Explosion Proof Fan - 3990 CFM - 1/2 HP - 115-230V - C1 Group D, C2 Groups F&G - 50 Hz
EPF-HPSM-18-0.5HP-50HZ



EPF-HPSM-18-0.5HP-50HZ Explosion Proof High Volume Ventilation Fan

Type: High Pressure High Volume Ventilation Fan
Propeller Dimensions: 18" Diameter
Propeller Material: Spark-Resistant Cast Aluminum
Weight: 55 lbs
Voltage: Multi-Voltage - 115-230V AC 50 Hz
Motor: 1/2 HP Fully Enclosed Explosion Proof
Rotations Per Minutes (RPM): 1750
Peak CFM (@ 0" SP): 3990
Max Sones @ 5': 23
Wiring: Hard-Wire
Mounting: Permanent Mount
Warranty: Yes - 1 Year*

Ratings/Features:

Listed for United States
Class I, Divisions 1 & 2, Group D
Class II, Divisions 1 & 2, Groups F & G
Spark-Resistant Propeller
Up To 3990 CFM Air Movement
Rated for Hazardous Environments
Made in the USA

Special Orders- Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-498-3363
E-mail: sales@larsonelectronics.com

Made in the USA

The EPF-HPSM-18-0.5HP-50HZ from Larson Electronics is a high pressure, high volume explosion proof ventilation fan that operates on 115-230V AC 50 Hz voltage. This high volume explosion proof ventilation fan features an 18" diameter spark resistant cast aluminum blade that moves air at a rate of up to 3990 cubic feet per minute (CFM) for superior ventilation and air movement. The EPF-HPSM-18-0.5HP-50HZ is powered by a fully enclosed and explosion proof 1/2 horsepower motor.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT

The EPF-HPSM-18-0.5HP-50HZ explosion proof fan is rated for Class I Group D and Class II Groups F & G hazardous environments. The 18" diameter propeller on this explosion proof high pressure ventilation fan is constructed from cast aluminum to resist sparking further increasing the safety of the hazardous environment in which the fan is being utilized. This single phase explosion proof ventilation fan has a 1/2 horsepower fully enclosed motor that can spin the propeller at a rate of 1750 RPM.

Voltage: The EPF-HPSM-18-0.5HP-50HZ explosion proof ventilation fan is multi-voltage capable and can operate on voltages ranging from 115-230V AC 50 Hz.

Wiring: The EPF-HPSM-18-0.5HP-50HZ is a hard-wired ventilation fan that should be installed according to national, state and local electrical and mechanical codes.

Applications: Class I Group D and Class II Groups F & G hazardous areas that require ventilation including but not limited to the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas.



At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Fully enclosed explosion proof 1/2 HP motor.
2. Spark-resistant cast aluminum 18" diameter propeller.
3. Class I Group D and Class II Groups F & G rated.
4. Multi-voltage capable.
5. Moves up to 3990 cubic feet of air per minute.
6. Fully assembled and ready to install

CFM Static Pressure (SP) Ratings

- 0" SP - 3990 CFM
2. 1/8" SP - 3780 CFM
3. 1/4" SP - 3480 CFM
4. 3/8" SP - 3020 CFM
5. 1/2" SP - 2250 CFM

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [DimensionalDrawing](#)
- [large](#)
- [medium](#)
- [SpecSheet](#)
- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)