Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671


www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-PT-100LED-RT

100W Explosion Proof Adjustable Pole Top Slip Fitter Mount LED Light Fixture - Slip Fitter Yoke

Product ID: 149959

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-PT-100LED-RT Pole Top Slip Fit Mount

Listing: United States - Canada
Lamp Type: Cree LED
Dimensions: 16"W x 22"H x 18"D
Weight: 42 lbs
Voltage: 120-277V AC or 11-25V DC
Total Watts: 100W
Total Lumens: 11,667
Luminous Efficiency: 116.67 Lm/W
Lamp Life: 60,000+ Hours
Color Temp: 5000K, 4000K or 3000K
Color Rendering Index: >75 CRI
Beam Angle: 60° or 125°
Lighting Configuration: Flood Pattern
Power Efficiency: >95%
Power Factor: 0.992
Ambient Operating Temp Range: -50°C to +65°C
Operating Temp Rating: T5
Lamp Housing Material: Copper Free Cast Aluminum
Lens Material: Hardened Borosilicate Glass
Mount Material: Non-Sparking Aluminum w/ SS Hardware
Gasket Material: Silicone
Mounting: Slip Fit Yoke Mount w/ Adjustable Bracket
Yoke Diameter: 1.5", 2", 2-1/4", 2-1/2", 2-3/4", 3" Slip Fit
Wiring: Flying Leads inside Junction Box
Wiring Hub: 3/4" NPT

Ratings/Approvals

Listed for United States and Canada
Class I, Divisions 1 & 2, Groups C and D
Class II, Divisions 1 & 2, Groups E,F,G
Class III, Divisions 1 & 2
Certified to UL 844 Ed. 13
Certified to UL 1598
Certified to C22.2 No. 137 Rev 2009
Certified to C22.2 No. 250.0
Certified to C22.2 No. 30-M-1986 Rev 2012
T5 Temperature Rating
Paint Spray Booth Approved
IEC 60529 Tested
IP67 Rated Waterproof
IP67 Rated Waterproof
Multiple Driver Banks
80% Lumen Retention after 60,000 Hours
Factory Sealed Light Fixture
Recommended 10` to 30` Mounting Height
120-277V AC or 11-25V AC/DC
Adjustable Swiveling Pole Top Mount
Multiple Slip Fit Yoke Diameters Available

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The EPL-PT-100LED-RT from Larson Electronics is a Pole Top Slip Fitter LED Light Fixture provides operators with a powerful and energy efficient alternative to traditional hazardous location luminaries. Cree LED technology and compact design makes this lamp an excellent replacement upgrade option for bulky and high maintenance cost older fixtures. This explosion proof slip fitter operates on 120-277V AC or 11-25V DC current.

This Class I Divisions 1 & 2, Class II Divisions 1 & 2 pole top slip fit mount explosion proof light fixture provides 11,667 lumens of high quality light while drawing only 100 watts. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. Special heat dissipating design in conjunction with LED technology helps this fixture to achieve an excellent 60,000 hour rated lifespan with 80% lumen retention. Light weight and a low profile make this unit an attractive alternative to larger and heavier older fixtures and requires less hardware to install.

The EPL-PT-100LED-RT pole top slip fit mount explosion proof light features an adjustable swivel bracket constructed of 3/8" aluminum that allows 270° of adjustment and is attached to a slip fit yoke for easy installation. The slip fit yoke is built to customer`s specs, enabling operators to mount this explosion proof LED light to their specific pole size. The wiring of the EPL-PT-100LED-RT is terminated in a junction box with 3/4" threaded hub. Operators can run rigid pipe or flexible conduit to the junction box, terminating the electrical connections within.



Click Photo to Enlarge



Click Photo to Enlarge

Click Photo to Enlarge



The explosion proof LED light fixture features multiple LED drivers which helps to increase the operational life of the fixture. With traditional LED lights, in the event an LED array or driver fails, the entire fixture no longer illuminates. This new series of LED lamps contains eight individual LED boards configured in a series of banks. Each bank contains two LED boards with an individual driver. In the event of a driver failure, only one bank of LEDs will be effected while the other banks will continue to operate. In the event that of an LED failure, the mating LED will continue to operate.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and

high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.
The aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LED luminaries. The LED lamp produces 11,667 lumens with a color temperature of 5000K, 4000K or 3000K and a color rendering index of 75 which produces colors and details much more accurately than high pressure sodium or mercury vapor luminaries. The lamp is T5 temperature rated, Design Lights Consortium approved, and the LED light head retains 80% of its lumen output after 60,000 hours of use, far longer than incandescent or fluorescent lamps.

Energy Consumption Comparison

	Metal Halide	LED
Wattage	250 watts	100 watts
Amp Draw @ 120V AC	2.38 amps	0.83 amps
Amp Draw @ 220V AC	1.30 amps	0.45 amps
Amp Draw @ 240V AC	1.19 amps	0.42 amps
Amp Draw @ 277V AC	1.03 amps	0.36 amps
Amp Draw @ 12V DC	23.75 amps	8.3 amps
Amp Draw @ 24V DC	11.88 amps	4.17 amps
Lamp Life Expectancy	20,000 hours	50,000+ hours
Operation cost per year (12hs/day @ 12c/kWh)	$149.80	$52.56

The EPL-PT-100LED-RT yoke mount explosion proof LED flood light is universal voltage capable and can be operated with 120-277V AC current without modifications. The EPL-PT-100LED-RT is also available in a 11-25V DC configuration. Please make your voltage configuration selection when ordering below. This explosion proof LED light fixture is IP67 rated, dust-proof, and protected against high pressure jets and temporary submersion. The cast aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LEDs and electronics.
The entire assembly is ETL listed Class I, Divisions 1-2 and Class II, Divisions 1-2 for use in hazardous locations and approved for paint spray booths. The extreme durability, universal voltage capabilities, and LED longevity make this LED flood lighting system an ideal fit for frac pads, rigs, offshore, and any application that requires a Class I Division 1 pole top light fixture.

Click Photos to Enlarge


60° Beam Angle


125° Beam Angle


140° Beam Angle

Beam Angles: When used as a portable lighting solution, the varying beam angles are each individually ideal for several environments. The 60° beam provides the most

intense beam of the three options. It is perfect for narrow, confined spaces and is ideally suited for tank cleaning purposes. It offers focused light to provide ample illumination to tight work spaces and other environments. The 125° beam offers a more diffused source of light that is also less intense in brightness. It is a great general area work light and performs well when used for outdoor illumination. The 140° beam offers a very wide lighting pattern and is ideal for situations where lighting distance is not a concern, but illumination of a wider area and even light distribution is. The 140° beam is great for situations that call for working in close proximity to lights such as in a paint booth.


Mounting Notes: The EPL-PT-100LED-RT pole top slip fit mount explosion proof light features an adjustable swivel bracket constructed of 3/8" aluminum that allows over 270° of adjustment and is attached to a slip fit yoke for easy installation. The slip fit yoke is built to customer`s specs, enabling operators to mount this explosion proof LED light to their specific pole size. For example, selecting a 2" OD mount means that the yoke mount will fit onto pipes or bull horns with a 2" OD.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.


Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671


www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-PT-100LED-RT

Product ID: 149959

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPL-PT-100LED-RT-Beam Angle-Mount-Voltage

Example: EPL-PT-100LED-RT-60B-1.5in-1227

Beam Angle	
60°	-60B
125°	-125B

Mount	
1.5	-1.5in
2	-2in
2 1/4	-2.25in
2 1/2	-2.5in
2 3/4	-2.75in
3	-3in
3 1/2	-3.5in
4	-4in

Voltage	
120-277V	-1227
-11-25V	-1224

Links (Click on the below items to view):

- SpecSheetSpanish
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- Video1
- Video2
- Video3
- Video4
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map