

EPLRL-LER-2X-20A-100-12.3-EPP

Explosion Proof Cord Reel - 100' 12/3 SOOW Cord - EXP Plug - 20A Cont. Service - (2) EXP Receptacles

Product ID: 150279

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLRL-LER-2X-20A-100-12.3-EPP Explosion Proof Cord Reel

Unit Type: Explosion Proof Cord Reel w/ Plug

Dimensions: -

Weight: -

Voltage: 125V or 250V

Amps: 20A Continual Service

Receptacles: (2) 20A, 3P2W, EPO-20A

Materials: Copper-free Aluminum

Hardware: Stainless

Cord: 100' 12/3 SOOW Cord

Plug: 20A, 3P2W, EPP-20A

Reel Mechanism: Manual Crank

Ratings/Approvals

Class I, Div 1 & 2 Groups C,D

Class II, Div 1 & 2 Group G

Class III

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPLRL-LER-2X-20A-100-12.3-EPP Explosion Proof Cord Reel extends electrical and power connections safely in flammable work sites. The manual-crank unit offers 20 amps of continual service and 100` of 12/3 SOOW cord with an explosion proof plug. Operators can access two explosion proof receptacles on the reel. This unit features

copper-free aluminum construction and stainless hardware.

The EPLRL-LER-2X-20A-100-12.3-EPP is a manual-crank operation cord reel for hazardous locations and combustible work sites. This unit provides 20 amps of continual service and access to two, 20-amp 3P2W explosion proof receptacles (EPO-20A). A 100' 12/3 SOOW cord with a 20-amp 3P2W explosion proof plug (EPP-20A) comes with the explosion proof cord reel. Voltage options include the following: 125V or 250V.

Built by Larson Electronics, the EPLRL-LER-2X-20A-100-12.3-EPP is constructed of copper-free aluminum with stainless hardware. This unit is suitable for Class I, Divisions 1 and 2, Groups C, D; Class II, Divisions 1 and 2, Group G; and Class III environments.

Inter-Compatibility: These plugs are cross-interchangeable with Appleton Powertite, Crouse Hinds Arktite, and Hubbell-Killark KR series plugs and receptacles. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your power and lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

EPLRL-LER-2X-20A-100-12.3-EPP

Product ID: 150279

Export Control Classification Number (ECCN): EAR99

Options:

EPLRL-LER-2X-20A-100-12.3-EPP-Voltage

Example: EPLRL-LER-2X-20A-100-12.3-EPP-2023-125V

Voltage	
125V	-2023-125V
250V	-2023-250V

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)