Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-TFM-100W-RD2-LED-TRC-100

100W Explosion Proof LED Light - C1D1 - C2D1 - Group B+ ATEX/IECEX - IP68 - Aluminum Triangle Mount

Product ID: 150531

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLX-TFM-100W-RD2-LED-TRC-100 Explosion Proof LED

Lamp Type: AC LED
Listing: United States, Canada, Europe
Dimensions: 18.09"L x 15.9"W x 23.75"H
Weight: 75 lbs
Voltage: 120V AC, 208V AC, 220V AC or 240V AC
Total Watts: 100W
Lumens: 10,500 (5000K) or 9,500 (3000K)
Luminous Efficacy: 105 Lm/W (5000K) or 95 Lm/W (3000K)
Lamp Life: 60,000+ Hours
Color Temp: 5000K cool white, 3000K warm white
Color Rendering Index: >70 CRI
Beam Angle: 110°
Lighting Configuration: Wide Flood Beam
Power Efficiency: >85%
Power Factor: >0.9
Amperage: 0.83A@120V AC, 0.48A@208V AC, 0.45A@220V AC, 0.41A@240V AC
Ambient Operating Temp Range: -60°C to +100°C
Operating Temp Rating: T6
Housing Material: Copper Free Cast Aluminum
Stand Material: Non-Sparking Aluminum
Lens Material: Hardened Borosilicate Glass
Mounting: Triangular Shaped Aluminum Base Stand
Finish: Powder Coated - Gloss Blue

Ratings/Approvals

Class I, Division 1, Groups B, C, D
Class II, Division 1, Groups E, F, G
UL 844
UL 60079
UL 1598
IEC Ex d IIB+H2
IEC Ex tb IIIC
IP68 Waterproof
NEMA 6/6P
Factory Sealed Light Fixture
ABS Type Approval

Special Orders - Special Requirements

Contact us for special requirements

Wiring: 100` 16/3 SOOW Cord
Cord Cap: 5-15 Straight (120V), 5-20 Twist (120V) or 6-20 Twist (250V) Explosion Proof Plug
Warranty: Yes - 5 Years*

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)






LARSON
ELECTRONICS



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-TFM-100W-RD2-LED-TRC-100

Product ID: 150531

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPLX-TFM-100W-RD2-LED-TRC-100-Voltage-Cord Cap-Color Temp

Example: EPLX-TFM-100W-RD2-LED-TRC-100-120V-1523-50K

Voltage	
120V	-120V
208V	-208V
220V	-220V
240V	-240V

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Color Temp	
5000K	-50K
3000K	-30K

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**