

EPL-TL-2XLE1-C-LV

Explosion Proof Two Color LED Light - C1D1/C2D1 Traffic Light - Signal Stack Light - ATEX Rated

Product ID: 150590

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-TL-2XLE1-C-LV Explosion Proof LED Traffic Light

Lamp Type: LED
Dimensions: -
Watts: 24W
Voltage: 12V DC or 24V DC
Lumens: 2,640 (1,320 lm per Lamp)
Luminous Efficacy: 110 Lm/W
LED Light Color: Green-Red, Red-White, Blue-White, Red-Amber or Blue-Green
LED Life Expectancy: 50,000 hours
Lighting Configuration: Steady Burn, Strobe or Strobe/Steady
Ambient Operating Temp Range: -40°C to +60°C
Housing Material: Aluminum
Lens Material: Polycarbonate
Mounting: Back Plate w/ Predrilled Aluminum Flat Surface Mounting Bracket
Wiring: 10' SOOW Cable w/ Flying Leads

Ratings/Approvals

Listed for United States, Canada, Europe, Asia
Class I, Div. 1 & 2, Groups A, B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Div. 1 & 2, Groups E, F, G
Class III, Div. 1 & 2
NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)
ATEX Ex II 2 G / D
IECEx db IIC Gb
IECEx tb IIC Db IP66

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in Texas

The EPL-TL-2XLE1-C-LV from Larson Electronics is an Explosion Proof Two Color LED Light designed for illuminative signaling in flammable work sites. The ATEX-rated traffic light is equipped with two LED lamps with

colored lenses, secured on a copper-free aluminum backplate. This 24-watt explosion proof system operates on 12V DC or 24V DC.

The EPL-TL-2XLE1-C-LV is a two-color LED signal light for combustible environments and ATEX-rated facilities. The explosion proof 24-watt unit consists of two explosion proof LED lamps with colored lenses, which are mounted on an aluminum backplate. Each LED fixture produces 1,320 lumens of high-intensity LED light for illumination within hazardous areas and potentially explosive work environments. This explosion proof LED system operates on 12V DC or 24V DC. The standard lamp configuration is red and green LED lamps in a steady burn or strobing configuration. The EPL-TL-2XLE1-C-LV is offered in the following color combinations: Green-Red, Red-White, Blue-White, Red-Amber or Blue-Green. We also offer a large assortment of lamp color options including red, green, blue, amber, purple and white LED lamps. Please contact us for special lamp configurations. These stack lights can also be configured with audible horns.

Commonly used color codes for indicators:

- **Red:** Stop / Failure conditions, such as an emergency stop or machine fault
 - **Yellow:** Caution / Warnings, such as over-temperature or over-pressure conditions
 - **Green:** Go / Normal machine or process operation
 - **Blue:** External help request / Operator/Supervisor required / Maintenance personnel assistance required
 - **White:** User-defined conditions specific to application and environment
-

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Durability: The LED signal lamps are rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining lightweight and easy to use. The units can operate in temperatures of -40° Celsius to 60° Celsius, are waterproof to 3 meter and resist ingress of dust, dirt and humidity. The housings are formed from

extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations.

Mounting/Wiring: Mounting is provided by a heavy gauge aluminum back plate fabricated from copper free aluminum with four predrilled holes designed to be bolted to walls, ceilings and flat surfaces for permanent and secure attachment. The ATEX-rated LED traffic light comes with 10` of SOOW cable w/ flying leads for completing electrical connections.

Applications: Flammable work sites, hazardous locations, safety lighting, traffic light, manufacturing facilities, chemical processing, signaling, warehouses and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



EPL-TL-2XLE1-C-LV

Product ID: 150590

Export Control Classification Number (ECCN): EAR99

Options:

EPL-TL-2XLE1-C-LV-Voltage-Beam Config-Colors

Example: EPL-TL-2XLE1-C-LV-12VDC-STB-GR

Voltage	
12V DC	-12VDC
24V DC	-24VDC

Beam Config	
STEADY BURN	-STB
STROBE	-STROBE
STROBE/STEADY	-STROBE-STB

Colors	
GREEN-RED	-GR
RED-WHITE	-RW
BLUE-WHITE	-BW
RED-AMBER	-RA
BLUE-GREEN	-BG

Links (Click on the below items to view):

- [Operations Manual](#)
- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)