

Spider Box - 125/250V AC Input - (6) 120V 20A GFCI Protected Duplex Outlets - 30A Plug

Part #: [WALSB-125.250.30A-6X120.20A-WP](#)



Made in Texas

The Larson Electronics WALSB-125.250.30A-6X120.20A-WP portable spider box has a 120V AC 50/60 Hz input voltage and features six 120V outlets for convenient use of up to 12 devices. This weatherproof portable spider box allows operators to plug into 125/250V generators and welding outlets via a 30-amp, L14-30P, 125/250V cord cap.

The WALSB-125.250.30A-6X120.20A-WP portable spider box from Larson Electronics is built to provide operators with a reliable source of 120V power. This compact spider box is designed for portability and convenience as well as durability. Featuring an elevated base platform for protection from standing water and weatherproof construction, the WALSB-125.250.30A-6X120.20A-WP is ideal for powering 120V equipment and lighting in construction, entertainment, job-site, marine, and outdoor locations where 120V generators are providing power.

This portable spider box features six duplex 120V 20A GFCI protected outlets that provide sealed and secure connections for up to 12 devices. In addition, the GFCI duplex receptacles provide 120V for powering high voltage lighting and equipment without the need for running additional extension cords. Each receptacle features a hinged watertight cover protecting the face from rain, water, and moisture when not in use. The WALSB-125.250.30A-6X120.20A-WP spider box features short circuit and overload protection. In the instance of circuit overload, the unit automatically shuts down to protect the spider box from damage and restarts after 30 seconds.

The housing on the WALSB-125.250.30A-6X120.20A-WP is constructed from powder coated steel with a NEMA 3R enclosure rating. The top of the unit features a convenient carrying handle that doubles for cable management when not in use. The angled base and low center of gravity ensure this low voltage transformer does not tip over when in the field. The entire unit is powder coated with glossy blue finish for corrosion resistances and aesthetics.

The WALSB-125.250.30A-6X120.20A-WP portable spider box system uses an input voltage of 120V AC brought in via 40' of four-conductor no.10 chemical and abrasion resistant SOOW cable that is fitted with a 30-amp, L14-30P, 125/250V cord cap. Output voltage of 120V AC is distributed via the six duplex 120V 20A GFCI protected outlets.

Larson Electronics is a manufacturer and as such can build transformers to your specifications. Although we carry several models of power distribution systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com.

Specifications / Additional Information**WALSB-125.250.30A-6X120.20A-WP Spider Box****Primary Voltage:** 120V AC 50/60 Hz**Line-In Cable:** 40' 10/4 SOOW Cable w/ Cord Cap**Line-In Cord Cap:** 30A L14-30P [125/250V]**Secondary Voltage:** 120V AC**Secondary Receptacles:** (6) 120V 20A GFCI Protected Duplex**Secondary Protection:** Ground Fault Circuit interrupter**Dimensions:** 15"L x 10.25"W x 25.38"H**Weight:** 24 lbs**Mounting:** Portable / Base Stand**Ratings/Approvals**

UL 508A

NEMA 3R Weatherproof

Overload Protection

Short Circuit Protection

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com

Larson Electronics manufacture a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Scroll Down to Purchase

This product does not qualify for free shipping.

Part #: WALSB-125.250.30A-6X120.20A-WP (150727)









Links (Click on the below items to view):

- [WiringDiagram](#)
- [Hi-Res Image 1 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 2 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 3 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 4 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 5 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 6 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 7 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 8 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)
- [Hi-Res Image 9 - Transformer - 120 volts AC to 12/24 volts DC - 6 twist lock outlets](#)