

**30 kVA Isolation Transformer - 415V Delta Primary to 208Y/120 Wye-N Secondary - NEMA 3R**

Part #: [MT-DOE16-3P-415D-30KVA-208Y.120-N3R](#)



The MT-DOE16-3P-415D-30KVA-208Y.120-N3R 415V Delta 3 Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-3P-415D-30KVA-208Y.120-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\***

**Transformer Features:** With a transformer rating of 30kVA, the MT-DOE16-3P-415D-30KVA-208Y.120-N3R isolation transformer is a three phase unit with a primary voltage of 415V Delta. It also provides a secondary voltage of 120/208Y Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP24.

**Benefits:** The MT-DOE16-3P-415D-30KVA-208Y.120-N3R isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

**Safety:** The MT-DOE16-3P-415D-30KVA-208Y.120-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-415D-30KVA-208Y.120-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

**Applications:** General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

#### **Specifications / Additional Information**

<b><u>MT-DOE16-3P-415D-30KVA-208Y.120-N3R Isolation Transformer</u></b>	<b><u>Ratings</u></b>
<b>Phase:</b> Three Phase	Listed for United States and Canada
<b>Frequency:</b> 60Hz	ANN Cooling
<b>kVA:</b> 30	IP24 Rated
<b>Primary Voltage:</b> 415V Delta	Isolation Transformer
<b>Primary Connection:</b> Delta	
<b>Primary BIL:</b> 10kV	
<b>Primary FCAN:</b> 2 x 2.5%	
<b>Primary FCBN:</b> 4 x 2.5%	
<b>Secondary Voltage:</b> 120/208Y Wye-N	
<b>Secondary Connection:</b> Wye-N	
<b>Secondary BIL:</b> 10kV	
<b>Winding Material:</b> Aluminum	
<b>Efficiency:</b> DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)	
<b>Insulation:</b> 220°C	

**Temperature Rise:** 150°C

**Impedance (Std):** 1.8% - 7.5%

**Seismic Zone:** Zone 4

**Sound Level:** Meets NEMA ST-20 Standards

**Termination:** Front Accessible Terminals

**Enclosure Material:** NEMA Type 3R Heavy Duty Ventilated

**Finish:** ANSI 61 Grey, UL50 Finish

**Dimensions:** 28.80"H x 25.80"W x 23.80"D

**Weight:** 310 lbs

**Mounting:** Floor or Wall

**Special Orders- Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-214-616-6180

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**-Scroll Down to Purchase-**

[This product does not qualify for free shipping.](#)

[Part #: MT-DOE16-3P-415D-30KVA-208Y.120-N3R \(150917\)](#)









Links (Click on the below items to view):

- [Manual](#)

- [WiringDiagram](#)

-

-

-

-

-