

GSLEDIP12-C1D2-1227-25C-EPP

8W LED Light Fixture - 13.4" Light Fixture - 25' 16/3 SOOW Cord w/ EXP Cord Cap

Product ID: 151064

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GSLEDIP12-C1D2-1227-25C-EPP Hazardous Location LED Lighting

Lamp Type: LED

Dimensions: Lamp 13.38"-L 2.68" -W 1.69"- D

Weight: 0.7 lbs | 0.3 kg

Watts: 8.4

Voltage: 120-240V AC

Lumens: 442

Lamp Life Expectancy: 100,000 Hours

CRI: 75

Amps: 0.66 A @12 VDC | 0.33 A @ 24 VDC

Light Color: 6500K

Beam Type: 100° Flood or 30° Spot

Mounting: 1/4" - 20 Screws /Aluminum 1" Yoke

Temp Range: -40°C – +85°C

Wiring: 25' 16/3 SOOW Cord w/ EXP Cord Cap

Cord Cap Options: 5-15P, 5-20P, 6-20P

Ratings

Class I, Div 2 Groups A,B,C,D

CSA 22.2 No. 250.0

UL 1598

IP54 Ingress Protection

T3 Temperature Rating

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)

GSLEDIP12-C1D2-1227-25C-EPP

Product ID: 151064

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GSLEDIP12-C1D2-1227-25C-EPP-Beam Config-Cord Cap

Example: GSLEDIP12-C1D2-1227-25C-EPP-SP-1523

Beam Config	
SPOT	-SP
FLOOD	-FL

Cord Cap	
5-15P	-1523
5-20P	-2023.125V
6-20P	-2023.250V

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)