Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-QP-120W-1XRD3-TRC-100

120W Explosion Proof LED Light Tower - C1D2, C2D2 - Quadpod Mount - ATEX/IECEx Rated - IP67

Product ID: 151161

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLX-QP-120W-1XRD3-TRC-100
Explosion Proof LED Light Tower

Lamp Type: AC LED
Listing: United States, Canada, Europe, Asia
Light Head Dimensions: 9.59"OD x 10.94"H
Tower Height: 7` to 12`
Voltage: 120V AC, 208V AC, 220V AC, 240V AC, 277V AC
Total Watts: 120W
Lumens: 12,600 (5000K) or 11,400 (3000K)
Luminous Efficacy: 105 Lm/W (5000K) or 95 Lm/W (3000K)
Lamp Life: 60,000+ Hours
Color Temp: 5000K cool white, 3000K warm white
Color Rendering Index: >70 CRI
Beam Angle: 110°
Lighting Configuration: Flood Beam
Power Efficiency: >85%
Power Factor: 0.9
Amperage: 1.16A@120V AC, 0.67A@208V AC, .63A@220V AC, 0.58A@240V AC, 0.50A@277V AC
Ambient Operating Temp Range: -60°C to +100°C
Operating Temp Rating: T6
Housing Material: Aluminum Alloy
Quadpod Material: Non-Sparking Aluminum Tubing w/ Rubber Casters
Lens Material: Tempered Glass

Ratings/Approvals

Class I, Division 2 Groups A, B, C, D
Class II, Divisions 2 Groups F, G
IEC Ex d IIB+H2 T6..T4 Gb
IEC Ex tb IIIC T105°C Db
ATEX II 2G Ex d IIB+H2 T6...T4 Gb
ATEX II 2D Ex tb IIIC T105° Db
IP67 Waterproof
NEMA 6/6P
Certified to UL 844
Certified to UL 1598
Certified to IEC 60079-0: 2011
Certified to IEC 60079-1: 2007-04
Certified to IEC 60079-31: 2008
Certified to EN 60079-0: 2012
Certified to IEC 60079-1: 2007
Certified to IEC 60079-31: 2009
Factory Sealed Light Fixture
Compatible With Lutron C.L. Series Dimmers
ABS Type Approval

Mounting: Extendable Quadpod w/ (2) Rubber Wheels
Wiring: 100` 16/3 SOOW Cord
Wiring Hub: 3/4" NPT

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The EPLX-QP-120W-1XRD3-TRC-100 from Larson Electronics is an Explosion Proof LED Light Tower that is a compact powerhouse ruggedly built to withstand demanding conditions. The EPLX-QP-120W-1XRD3-TRC-100 features state-of-the-art AC LEDs paired with specially designed heat sinks for improved efficiency, thermal management, and durability. Available in 5000K warm white and 3000K cool white options, this sleek and modern fixture delivers brilliant illumination and maximum efficiency. Designed for elevated illumination, this explosion proof LED light tower is mounted on a quadpod. The tower retracts to 7 feet and extends to 12 feet (maximum).

Light Features: With a compact pendant mounted design and sleek body, the EPLX-QP-120W-1XRD3-TRC-100 provides brilliant illumination and robust performance in an aesthetically appealing package. Available in 5000K warm white and 3000K cool white options, the 110° flood beam provides crisp, clean illumination. The 120-watt LED lamp is mounted on a quadpod with two rubber wheels, which can extend from 7 feet to 12 feet. This unit offers up to 12,600 lumens of output @ 5,000K and is equipped with 100` of 16/3 SOOW cord.

IP67 rated construction means the EPLX-QP-120W-1XRD3-TRC-100 LED light mast is tough enough to withstand the corrosive effects of harsh outdoor conditions, including sun, wind, rain, sleet, snow, and saltwater spray. This fixture is completely protected against the ingress of dust, dirt, and humidity as well as withstand the corrosive effects of saltwater spray and harsh outdoor conditions. Housed within a corrosion resistant aluminum alloy body and protected by a tempered glass lens, the EPLX-QP-120W-1XRD3-TRC-100 features the added bonus of a dust and buildup rejecting exterior coating.

The EPLX-QP-120W-1XRD3-TRC-100 utilizes AC LEDs paired with a heavy-duty housing and an advanced heat sink that allows for improved efficiency and thermal performance. By eliminating the drivers associated with DC LEDs, space is freed up for more connective surface, accelerating heat dissipation and increasing durability. The specially designed heat sink allows for greater surface area contact with the air as well as a stronger airflow rate. Because this fixture is created for maximum thermal efficiency, it is ideal for applications in which the ambient operating temperature falls into extreme ranges, especially high heat applications. Furthermore, fewer sub-components also means fewer chances for secondary component failure. The simplified circuit system used within AC LEDs creates greater stability and enhances luminaire lifespan.

Dimming: The EPLX-QP-120W-1XRD3-TRC-100 can be wired with a dimmer switch for dimming capabilities. This gives operators the ability to manually adjust the brightness of the LED lamp quickly and easily. When using an electronic dimmer switche, the EPLX-QP-120W-1XRD3-TRC-100 will dim from 0% up to 100% via the user provided dimming switch. This explosion proof LED light fixture is compatible with Lutron C.L. series dimmer switches. Compatible dimmers in that series include the following: Diva® C•L® dimmer, Ariadni®/Toggler® C•L® dimmer, Luméa® C•L® dimmer, Maestro® C•L® dimmer and Skylark® C•L® Dimmer.

PLEASE NOTE THAT ANY DIMMER INSTALLED ON THIS FIXTURE MUST BE LOCATED OUTSIDE OF THE HAZARDOUS AREA

The EPLX-QP-120W-1XRD3-TRC-100 is listed for use in the United States and Canada and carries IECEx and ATEX certifications.



Click Photo to Enlarge

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.
LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.
Mounting: This portable LED light is comprised of an LED light head mounted atop a four-leg quadpod fabricated from non-sparking powder coated aluminum. This adjustable and collapsible quadpod can be extended to twelve feet, collapsed to seven feet and includes solid wheels, allowing operators to tilt the unit back and simply roll the entire assembly to a new location when fully deployed.
Power/Wiring/Plug: The EPLX-QP-120W-1XRD3-TRC-100 is available in the following voltages: 120V AC, 208V AC, 220V AC, 240V AC, and 277V AC.
Suggested Applications: Oil refineries, petrochemical plants, offshore rigs, painting facilities, and the transportation of natural gas and liquefied petroleum gas.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-QP-120W-1XRD3-TRC-100

Product ID: 151161

Export Control Classification Number (ECCN): EAR99

Options:

EPLX-QP-120W-1XRD3-TRC-100-Voltage-Cord Cap-Color Temp

Example: EPLX-QP-120W-1XRD3-TRC-100-120V-1523-30K

Voltage	
120V	-120V
208V	-208V
220V	-220V
240V	-240V
277V	-277V

Cord Cap	
5-15P	-1523
5-20P	-2023-125V
6-20P	-2023-250V

Color Temp	
5000K	-30K
3000K	-50K

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map