

HALP-EMG-24-2L-BX-55W-3HR

110W Hazardous Location Light Emergency Backup Fixture, Non-Metallic, (2) 2' Bi-axial Compact Fluorescent Lamps, 3 Hour Battery Runtime, Corrosion Resistant, Marine Application, C1D2/C2D2

Product ID: 151271

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HALP-EMG-24-2L-BX-55W-3HR - Hazardous Area Fluorescent Light Emergency Fixture

Listing: United States - Canada

Lamp Type: 2' Bi-Axial Fluorescent

Dimensions: 25.88"-L x 8.25"-W x 7.00"-H

Weight: 8 lb

Voltage: Universal 120-277V AC, 50/60 Hz

Total Watts: 110W

Total Lumens: 5,600

Lumens Under Battery Power: 900

Lamp Life (Hours): 20,000

Efficiency (Lumens per Watt): 75

Color Temp: 4100K

Replacement Lamp: -

Beam Angle: 160° Horizontal, 116.5° Vertical

Dimming Function: No

Lighting Configuration: Flood

Power Efficiency: -

Power Factor: -

Ambient Operating Temp Range: -20°C to +70°C

Battery AC Input Voltage: 120/277V AC 60 Hz

Battery AC Input Current: 90 mA

Battery AC Input Power Rating: 9.5W

Ratings/Approvals

Listed for United States and Canada

Class I, Division 2, Groups A, B, C, D

Class II, Division 2, Groups F, G

NRTL Certified to UL 844

NRTL Certified to UL 924

NRTL Certified to UL 1598A Marine Type (Saltwater)

NRTL Certified to C22.2 No. 137

NRTL Certified to C22.2 No. 250.0

Meets USCG Specifications

California Title 24 Compliant

T6 Temperature Rating

Non-Corrosive Construction

Non-Metallic Housing Pan & Lens

Made in the USA

BAA Compliant

Silicone Free

CE Certified

Field Serviceable

Failsafe Lighting

Emergency Battery Backup

180+ Minute Runtime

Battery Output Current: 120V @ 165mA - 277V @ 72mA
Illumination Time: 90+ Minutes
Battery Type: High Temp, Maintenance Free, Nickel Cadmium
Battery Lifespan: 7 to 10 Years
Battery Charge Current: 250 mA
Battery Recharge Time: 24 Hours
Ambient Operating Temp Range: 0°C to +50°C
Operating Temp Rating: T6
Minimum Operating Temp: 0°C
Maximum Case Temp: +50°C
Housing Material: Fiberglass Reinforced Polyester Housing
Lens Material: Shatter/Impact Resistant Acrylic Diffuser
Gasket Material: Neoprene
Mounting: Flange Type Surface Mount or Pendant Mount
Wiring Hub: 1/2" or 3/4" NPT

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The HALP-EMG-24-2L-BX-55W-3HR from Larson Electronics is a Hazardous Area Fluorescent Light Emergency Fixture that is U.S./Canada approved Class I Division 2 Groups A, B, C and D and is specifically designed to handle the rigors of wet and corrosive marine environments. This hazardous location fluorescent light has a T6 temperature rating and carries a United States Coast Guard approval, making it ideal for applications such as oil rigs, ships, offshore applications, petrochemical, manufacturing, chemical storage, and water treatment centers.

The HALP-EMG-24-2L-BX-55W-3HR is a 24" long hazardous area compact fluorescent light fixture designed for use in wet areas and saltwater-marine environments where corrosion resistance is critical to equipment longevity and safety. This biaxial light fixture contains 2 compact fluorescent lights, produces 6,000 lumens at only 80 watts, and is designed to be a more energy efficient alternative to traditional incandescent lamps. This Class I Division 2 rated fixture is constructed of non-corrosive materials including a polyester housing reinforced with glass fiber, a poured in gasket for reliable sealing, and an impact resistant acrylic diffuser. Corrosion resistant plastic latches secure the lamp cover to the housing and provide a firm lock against the poured in seal to prevent drips and water intrusion.

This fluorescent light works, mounts, and is wired like our HALP-24-2L-BX explosion proof fluorescent light fixtures. The main difference is that we add a battery backup unit that adds emergency light functionality to the fixture. This hazardous area emergency light will run for 3 hours after power is lost. The light recharges the battery once electrical power is restored. Standard configuration includes a single emergency ballast that will run a single lamp at 900 lumens for 3 hours. The battery backup unit includes a switched leg for turning the light fixture on/off without kicking the unit into emergency mode.



HALP-24-2L



HALP-24-2L Surface Mount

[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

HALP-24-2L Pendant Mount

[Click Photo to Enlarge](#)

HALP-24-2L with T8 lamps

[Click Photo to Enlarge](#)

HALP-24-2L with T5HO lamps

[Click Photo to Enlarge](#)

The HALP-EMG-24-2L-BX-55W-3HR is NRTL Listed to UL 844 for Class I Division 2, Groups A, B, C, D hazardous locations. This fixture is also NRTL Listed to UL 1598A for outdoor marine type luminaires, and meets US Coast Guard specifications. This light fixture offers the extreme durability in a proven hazardous location fixture design, making it a reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present.

[Click here to read the NEC description for explosion proof and hazardous locations.](#)

Mounting Options: Unless otherwise specified, our standard, most popular configuration is the flange mount shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.



[Click Photo to Enlarge](#)

Standard Flange Brackets: Flange type aluminum mounts attached at each end of the fixture enables it to be simply secured to any surface. The mounts provide some shock absorbency protection while enabling the user to simply mount the fixture with the through-hole taps that protrude on each side of the fixture. The mounting holes are 14.91" inches on center apart along the top of this hazardous location light. The mounting holes are 9.5" inches on center across the top of the light.



[Click Photo to Enlarge](#)

Standard Suspension Mounting: This light fixture can hang from the ceiling suspended by rigid pipe. Each fixture is equipped with either two 1/2" or 3/4" NPT hubs on either side of the fixture. Operators will bring rigid pipe down to the threaded mounting ups. The wiring is fed down through the rigid pipe to one of the NPT hubs and tied to the fixture's lead wires to complete the electrical connection. The remaining pendant hub provides support for the opposite end of the fixture.

Suggested Applications: The HALP-EMG-24-2L-BX-55W-3HR is designed for marine wet and damp locations, where corrosion resistant fluorescent lights are required. This includes petrochemical facilities, lubrication pits, oil drilling rigs, crew quarters, solvent/cleaning areas, water treatment areas, processing plants, and marine loading docks.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

HALP-EMG-24-2L-BX-55W-3HR

Product ID: 151271

Export Control Classification Number (ECCN): EAR99

Options:

HALP-EMG-24-2L-BX-55W-3HR-Mount-Hub Config

Example: HALP-EMG-24-2L-BX-55W-3HR-SFC-0.5IN

Mount	
SURFACE	-SFC
PENDANT	-PND

Hub Config	
1/2IN	-0.5IN
3/4IN	-0.75IN

Links (Click on the below items to view):

- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)