Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-SM-24-WC-15C-2023

24" Explosion Proof Fan on Stand - Swivel Casters - 7980 CFM - 24IN - Pedestal - 15' Cord - 20A Plug

Product ID: 152711

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-SM-24-WC-15C-2023 Hazardous Location Fan
Unit Type: Hazardous Location Fan (Circular Pedestal)
Dimensions: 24" (Blade Diameter)
Weight: 78 lbs
Voltage: 115V or 208-230V
Start-up Amps: 9.8A @ 115V, 4.9A @ 208-230V
Motor: 0.50 Horsepower
Phase: 1

Rotations Per Minute (RPM): 1,725
Blade Pitch: 14 Degrees

CFM Delivery: 7,980
Blade Material: Aluminum
Fan Material/Finish: Powder Coated Steel
Wiring: 15` 16/3 Cable with Explosion Proof Plug
Cord Cap: 5-20P (125V), 6-20P (250V)
Blade/Fan Color: Metallic/Black

Ratings
Class I, Division 1
Class II, Division 1
Direct Drive
Thermal Protection
Four Anti-Static Swivel Casters

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in Texas

The Larson Electronics EPF-SM-24-WC-15C-2023 hazardous location fan with swivel casters is designed as a portable spot cooling fan for use in hazardous atmospheres. This Class I Division 1, Class II Division 1 fan is rated for use in atmospheres that include flammable or explosive vapors, gas, or dusts. Three aluminum fan blades angled at 14 degrees (pitch)

offer direct cooling in hazardous locations. The EPF-SM-24-WC-15C-2023 24" circulation fan comes with a 15` 16/3 SOOW cable and an explosion proof plug for connection to power sources.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT

This hazardous location fan is equipped with a robust design that is intended to minimize ignition or explosion in the applicable hazardous environment. It is important to note that no fan can be completely explosion proof. However, the EPF-SM-24-WC-15C-2023 hazardous location fan has all the design elements that minimize that risk including aluminum blades and a thermally protected, maintenance free 1/2 HP motor. This fan features two swivel casters in the front and two stationary casters in the back made with anti-static stainless steel hardware for seemless wheeling around the workplace.

This hazardous location pedestal fan has a 24" diameter and generates over 7,980 CFM of air output for efficient spot cooling. The EPF-SM-24-WC-15C-2023 fan is available in 115V operating at 9.8 amps or 208-230V operating at 4.9 amps. The powder coated steel fan guards offer corrosion resistance and a high degree of durability while the heavy-duty pedestal stand offers a sturdy base. The explosion proof fan weighs 78 pounds, spins at 1,725 RPM and is equipped with 15` of 16/3 SOOW cable and explosion proof plug.

Cord Options: The Larson Electronics EPF-SM-24-WC-15C-2023 hazardous location fan is outfitted with 15` of 16/3 SOOW cable and an explosion proof plug. The 115V model is equipped with a 5-20P explosion proof plug while the 208-230V model is equipped with a 6-20P explosion proof plug.

Click Photos to Enlarge



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring & Plug: This hazardous location fan is equipped with 15 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-20P 20 amp straight blade plug for use with 125V explosion proof outlets, or a 6-20P 20 amp straight blade plug for use with 250V explosion proof outlets.

Applications: Hazardous locations, industrial sites, oil and gas facilities, processing plants, construction, aerospace facilities, indoor/outdoor cooling systems and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPF-SM-24-WC-15C-2023

Product ID: 152711

Export Control Classification Number (ECCN): EAR99

Options:

EPF-SM-24-WC-15C-2023-Cord Cap

Example: EPF-SM-24-WC-15C-2023-125V

Cord Cap	
5-20	-125V
6-20	-250V

Links (Click on the below items to view):

- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- SpecSheetSpanish
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- Video1
- Video2
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map