

EXP-QD-SS-30P-1.5-S-PR-RC

Panel Mount Flameproof Receptacle - 30-pin Connector - Stainless Steel -

ATEX/IECEX/EAC/INMETRO/NEC5

Product ID: 152761

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-QD-SS-30P-1.5-S-PR-RC Panel Mount Receptacle

Unit Type: Flameproof Bulkhead Receptacle

Dimensions: 3.18" x 2.32"

Weight: -

Voltage: 600V Rated

Max Amps: 125A Rated

Configuration: 30-pin Connector (30 x 1.5mm² + Earth)

Ambient Temp Rating: T5 +40°C

Materials: Stainless Steel

Termination Style: Crimp

Mount: Panel

Cover: Flameproof Receptacle Cap

Ratings

II2 GD Exdb IIC Gb

Extb IIIC Db T95

ATEX/IECEX/EAC/INMETRO

DTS01 Deluge Protected

NEC 505

IP66/IP67

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EXP-QD-SS-30P-1.5-S-PR-RC Panel Mount Flameproof Receptacle is designed for electrical connections in flammable, ATEX/IECEX rated facilities. This panel mount receptacle contains a 30-pin connector configuration. The 600V and 125-amp rated unit is constructed of stainless steel and features protection via a flameproof receptacle cap.

The EXP-QD-SS-30P-1.5-S-PR-RC is a panel-mount, bulkhead receptacle with flameproof properties. This unit is rated for 600V and features a 30-pin connector

configuration. Equipped with a maximum rating of 125 amps, the device is protected by a flameproof receptacle cap. This unit is constructed of stainless steel and contains a crimp termination style. Compatible with panel mount applications, the IP66/IP67 rated receptacle can be used in ATEX/IECEX combustible environments.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

EXP-QD-SS-30P-1.5-S-PR-RC

Product ID: 152761

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)