Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-LTL-60W-LED-12VDC

100 Watt High Intensity LED Light - 8,100 Lumens - 12V DC - High Mast Lighting - Outdoor Rated

Product ID: 152907

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-LTL-60W-LED-12VDC High Mast LED Light
Lamp Type: CREE® LED
Dimensions:9"-L x 7"-W x 3"-D
Weight: 10 Lbs
Total Watts: 100
Total Lumens: 8,100
Luminous Efficiency: 81 lm/w
Beam Configurations: 10° Spot, 24° Wide Spot, 38° Narrow Flood, 60° Flood, or 90° Wide Flood
LED Color Temperature: 3000K, 4000K, 5000K, 6500K
LED Life Expectancy: 80,000 hours
Optics Efficiency: 98% - PMMA High Transmittance Optics
Led Drive %: 90%
Voltage:12V DC
Amp Draw: 5.5 @12V DC
Wiring: 2.5` Pigtail w/ Flying Leads
Mounting: Flat Surface Trunnion Mount U-Bracket
Materials: Die Cast Aluminum Housing, PMMA Optics
Housing Color: Powder Coated Black
Ambient Temperature Range: -40°C to +80°C
Waterproof Rating: IP67

Quick Summary
250 Watt Metal Halide Replacement
Ambient Op Temp -40C to +80C
Ideal for Light Towers & LED Retrofits
98% Transmission High Purity PMMA Optics
Multiple LED Banks for Heat Dispersion
81 Lumens Per Watt Efficiency
70% Lumen Retention after 80,000 Hours
UL1012 Compliant
UL60950-1 Compliant
CE Certified
RoHS Compliant
IP67 Rated Waterproof

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The GAU-LTL-60W-LED-12VDC High Mast LED Flood Light offers intense light output and is ideal for flood lighting, high mast lighting, light towers, as well

as industrial and outdoor lighting applications. Producing 8,100 lumens, a 0.84 amp draw at 12V, 80,000 hour service life, 120-277 volt compatibility, and IP67 waterproof rating, this LED flood light provides operators with a rugged and powerful LED alternative to 250 watt metal halide lamps that uses little power and can withstand rugged use and abusive conditions.

The GAU-LTL-60W-LED-12VDC LED light from Larson Electronics produces 8,100 lumens of high intensity light while drawing only 100 watts at 5.5 amps from at 12 volt electrical system. Six CREE® high output LEDs producing 1,350 lumens each are arranged in rows and paired with PMMA high purity optics to produce a well focused 24° wide spot beam that is ideal for providing far reaching concentrated illumination while still covering a substantial amount of area. We also offer optional optics with 10° spot, 38° narrow flood, 60° flood, and 90° wide flood beam spreads. The spot beams are tightly focused and are designed for high elevation mounting to achieve distance, making spot versions ideal for high mast and spots lighting. The flood beams are designed to provide more light over a larger area nearer the fixture, making flood versions ideal for use as dedicated work and area lights.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

GAU-LTL-60W-LED-12VDC lights are ideal replacements for fragile and hot running 250 watt metal halide lamps. They offer low power requirements, high durability and a versatile mounting system that makes these LED light emitters a superior lighting solution for demanding applications where power and reliability is critical. The heavy duty design and high power of these LED lights also makes them suitable for a wide array of applications including but not limited to: high mast lighting, light towers, light plant LED retrofits, military, mining, industrial manufacturing, machine visioning, security and law enforcement, commercial structure illumination, sport complexes, billboards, race tracks, and parking lots to name a few.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units feature individual heat sinks per bank of six LEDs to control heat buildup rather than utilizing a single housing to dissipate heat. This allows for more thorough cooling of the LEDs for extended operating periods. This allows the LEDs to be driven at up to 90% capacity without overheating or visible loss of light output. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 80,000 hours.

Durability: As well as unparalleled heat control, the GAU-LTL-60W-LED-12VDC series of LED lights from Larson Electronics also offer IP67 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can

withstand rapid temperature changes of -40° Celsius to +80° Celsius, are waterproof, and resist ingress of dust, dirt and humidity. The housings are formed from die cast aluminum and the optics are high transmission PMMA with 98% light transmittance. The CREE® LEDs help these units achieve resistance to vibrations and are rated at 70% lumen maintenance after 80,0000 hours of use. We recommend these LED lights for use in applications where a lot of vibration, dust, dirt, dampness and abusive working conditions are encountered.

Mounting: Each unit is equipped with a back mount trunnion style mounting bracket that allows the light to be attached to flat surfaces and adjusted through 160° of vertical movement. To adjust the unit after mounting, the user simply loosens the set screws located on either side of the unit, moves it into the desired position, then re-tightens the screws. The base of the mounting trunnion is equipped with several machined slots which allow users to utilize existing mounting holes and slide the unit for precise mount positioning.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-LTL-60W-LED-12VDC
Product ID: 152907

Warranty: 36 Months

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
GAU-LTL-60W-LED-12VDC-Option 1-Option 2
Example: GAU-LTL-60W-LED-12VDC-10SP-30K

Option 1	
10° SPOT	-10SP
24° WIDE SPOT	-24WS
38° NARROW FLOOD	-38NF
60° FLOOD	-60F
90° WIDE FLOOD	-90WF

Option 2	
3000K	-30K
4000K	-40K
5000K	-50K
6500K	-65K

Links (Click on the below items to view):

- **Beam Information (Coverage, Datafile)**
- **IES (Photometric File)**
- **Photometric Flood Report**
- **Photometric Indoor Report**
- **Photometric Polar Graph**
- **Spectrum Curve (Wavelength Graph)**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **HigResPic10**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**