Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXPCMR-ALG-1080P-SGM-1227

Explosion Proof 1080p Analog Portable Observation Camera - Day/Night Infrared - Sight Glass Mount

Product ID: 153144

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-ALG-1080P-SGM-1227 Explosion Proof Remote Observation Camera
Dimensions: 8"L x 6"W x 9"H
Camera Weight: 8 lbs
Total Watts: 3.5W Max
Voltage: 100-240 V 50/60Hz (primary), 12 V DC (secondary)
Video Framerate: 1080p @ 30fps
Image Sensor: 1/2.7" Progressive Scan CMOS
Signal System: NTSC
Effective Pixels: 1930(H) * 1088(V)
Min. Illumination: 0.1 Lux @ F1.2 AGC On / 0 Lux w/ IR
Shutter Speed: 1/30s to 1/50,000s
Lens: 3.6mm
Angle of View: 90°
Day/Night: ICR
Infrared Range: Up to 50`
D/N Mode: Color / BW/ Auto / EXT
White Balance: Auto / User / Push / 8000K / 6000K / 4200K / 3000K
Privacy Mask: On/Off, maximum 2 zones
Motion Detection: On/Off, maximum 4 zones
Blacklight Compensation: Support
Anti-flicker: On/Off
Display Functions: Digital noise reduction, Mirror
Video Output: (1) Analog HD Output
Protocol: Coaxitron
Signal to Ratio: >52 dB
Language: English

Quick Summary
Class I, Divisions 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Divisions 1 & 2, Groups E, F, G
Class III, Divisions 1 & 2
Ex db IIC Gb
Ex tb IIC Gb Db IP66
NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

Ambient Temperature Range: -10°C to +50°C
Housing Materials: Aluminum
Lens Material: Tempered Glass
Mounting: Adjustable Sight Glass Mount
Power Connection: Terminal Strips, Customer Provided Cord
Signal Connection: BNC Connector, Customer Provided Cord
Wiring Hub: (2) 3/4" NPT
Wiring: Customer Provided 2-Conductor Cable & Coax Cable

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The EXPCMR-ALG-1080P-SGM-1227 explosion proof high definition analog camera from Larson Electronics is an inspection camera that can be used for remote observation in hazardous locations. Designed for sight glass applications, the unit is available in a fixed lens configuration, a 3.6mm 90° lens to capture large wide areas, and can produce an image up to 1080p resolution. The EXPCMR-ALG-1080P-SGM-1227 allows operators to see visual process data from a centralized control room up.

Camera Features: The EXPCMR-ALG-1080P-SGM-1227 portable explosion proof camera is designed to allow operators to have a live feed from inside a tank, reactor, vessel or other workplace observation in hazardous locations. The explosion proof camera is incredibly durable and ready to be deployed in many different workplace conditions. The camera is operated remotely from a centralized control room which saves both time and money as well as contributing to workplace safety.

This explosion proof camera features an infrared LED array to allow for low light and nighttime visibility. The camera will automatically switch over to IR mode when lux levels drop below a preset level. This allows operators to has up to 50` of visibility in the dark. True day/night infrared cutoff filter removal creates a crisp, sharp image that transmits with zero latency to HD resolution via metal clad coax cable to customer provided remote mount DVR systems.

This remote inspection camera features a pressure-resistant 316 stainless steel body and weighs just under 4.5 pounds. The camera itself features 1 lux sensitivity, a 2-wire transmitter and a polished stainless steel mounting bracket as well as a built-in color CCD camera and a 1/3" CCD sensor. The lens of the EXPCMR-ALG-1080P-SGM-1227 features a viewing angle between 28° and 60° and the minimum lens to object distance is 3.15 inches.

Wiring: Link-up with the camera is achieved via customer provided coax cable with BNC connector through a 3/4" NPT. The cable is ran back to the customer provided DVR system, mounted outside the hazardous location. Terminal strips within the camera allow customers to terminate the power supply for the camera through a separate 3/4" NPT. This unit operates on universal voltage 120/240V AC 50/60 Hz.

Mounting: Equipped with adjustable legs at both sides of the unit, the EXPCMR-ALG-1080P-SGM-1227 Network Explosion Proof Camera is compatible with several mounting requirements and configurations. For sight glass/surface mounting, the device can be attached directly using a nut, flanged adapter collar or hinged bracket. Bracket components allow robust, angled positioning of the light head. The ATEX rated fixture supports compatibility with circular sight glass fittings (DIN 28120, DIN 28121), weld-neck type MV sight glass fittings, ANSI flange types and visual flow indicators.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, monitoring of cleaning, spray patterns, mixing, foaming, reaction, and level.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364







EXPCMR-ALG-1080P-SGM-1227

Product ID: 153144

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- ATEX Certificate (European Explosion Proof)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- Certificate 4, Misc
- Dimensional Drawing 2D
- Eye Safety Information/Certificate
- IEC Ex Certificate (International Explosion Proof)
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- SpecSheetSpanish
- STEP File (3D CAD Model)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map