Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-QC-QP-1X150LED-RT-100

150W EXP LED Light - 21,000 Lm - Tripod - Quick Change Mount - C1D1 - 100' 16/3 SOOW - GEN Plug

Product ID: 153192

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-QC-QP-1X150LED-RT-100

Lamp Technology: LED
Dimensions: 96.83"H x 87.66"W x 75.92"D (6.8` - 9.42` Total Height)
Weight: 75 lb
Voltage: 120-277 VAC, 50/60Hz
Total Watts: 150 Watts
Lamp Watts: 150 Watts
Total Lumens: 21,000
Lamp Lumens: 21,000
Luminous Efficacy: 140 Lm/W
Beam Lux: 8500 @ 1 Meter, 1250 @ 3 Meters
Lamp Life Expectancy: 60,000+ hrs
Color Temperature: 5600K, 5000K, 4500K, 4000K, 3500K, 3000K, 2700K, or 6500K
Light Color: Cool White, Neutral White, or Warm White
Color Rendering Index: >75 CRI
Beam Angle: 60°, 125°, or 140°
Lighting Configuration: Flood
Power Efficiency: >95%
Power Factor: 0.992
Ambient Operating Temp Range: -50°C to +65°C
Operating Temp Rating: T5
Ingress Protection Rating: IP67
Housing Material: Copper Free Cast Aluminum
Housing Finish: Epoxy Powder Coated - Grey

Ratings/Approvals

Listed for United States and Canada
Class I, Divisions 1 & 2, Groups C and D
Class II, Divisions 1 & 2, Groups E, F and G
Class III, Divisions 1 & 2
Certified to UL 844 Ed. 13
Certified to UL 1598
Certified to C22.2 No. 137 Rev 2009
Certified to C22.2 No. 250.0
Certified to C22.2 No. 30-M-1986 Rev 2012
T5 Temperature Rating
Paint Spray Booth Approved
IEC 60529 Tested
IP67 Rated Waterproof
Multiple Driver Banks
80% Lumen Retention after 60,000 Hours
Factory Sealed Light Fixture
3.5kV Surge Protection (NTC Circuit)
Quick Change Mounting System

Lens Material: Hardened Borosilicate Glass
Gasket Material: Silicone
Mount Material: Non-Sparking Aluminum
Mount Finish: Powder Coated - Gloss Blue
Mounting: Adjustable 6.8`-9.42` Tripod w/ Quick Change Disconnect Mount
Wiring Hub: 3/4" NPT
Wiring: 100` 16/3 SOOW Cord Terminated w/ General Area Straight Blade Plug
Cord Cap Options: 5-15, 6-15, 5-20, 6-20, L5-15, L6-15, L5-20, L6-20, BS1363, Schuko, or Pigtail

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-QC-QP-1X150LED-RT-100

Product ID: 153192

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPL-QC-QP-1X150LED-RT-100-Beam Angle-Color Temp

Example: EPL-QC-QP-1X150LED-RT-100-60B-56K

Beam Angle	
60°	-60B
125°	-125B
140°	-140B

Color Temp	
5600K	-56K
5000K	-50K
4500K	-45K
4000K	-40K
3500K	-35K
3000K	-30K
2700K	-27K
6500K	-65K

Links (Click on the below items to view):

- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- Dimensional Drawing 2D
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- STEP File (3D CAD Model)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- Video1
- Video2
- Video3
- Video4
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map