Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-ANC-48-160W-LED

160W High Bay LED Fixture - Low Profile, General Area Use - Modbus TCP/IP Network

Product ID: 153690

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-ANC-48-160W-LED 4` LED High Bay Linear

Lamp Type: LED
Dimensions:50"-L x 9"-W x 6"-H
Weight: 10 lbs
Total Watts: 160 watts
Voltage: 120-277V AC 50/60 Hz or 12-24V AC/DC - 347-480V AC optional
LED Lamp Life Expectancy: 50,000+ Hours
Beam Angle: 160°
Luminous Efficiency: 160 lm/w
Total Lumens: 19,200
Color Temp: 6000K
Ambient Temp Range: -30°C to +60°C
Power Efficiency: >90%
Power Factor: >0.95
Mounting: Surface Mount Brackets
Wiring: 10` Whip w/ Flying Leads
Materials: Aluminum Housing / Polycarbonate Lens

Features

1:1 Direct Replacement for 4` 4L T5HOs
50,000+ Hour LED Life Span
80% Lumen Retention after 50,000 Hours
Reduced Energy Consumption With Improved Output
Vapor Proof
Vibration Shock Resistant
IP65 Rated Waterproof
Outdoor Approved
Password Protected Network Controls
No Programming Required
Modbus TCP/IP Connectivity

Network Controller Specs

Dimensions: 1.41" x 3.88" x 3.1"
Weight: 5 oz
Network Type: 10/100 Base-T Ethernet Port

Protocols: HTTP, XML, Modbus TCP/IP

Power Supply: 9-28V DC

Digital Input: (1) Optically Isolated 4-26V DC

Current: 950uA @ 4V, 8.5mA @ 26V

Relay Contacts: (1) SPDT - 240V AC/30V DC Max @ 12A

Relay Modes: On/Off or Pulsed

Pulse Timer Duration: 0.1 to 86,400 Seconds

Input Functions: Monitor, Local Relay Control, Remote Relay Control

LED Indicators: (4) Digital Input Voltage Applied, Relay Coil Energized, Network Linked, Network Activity

Operating Temperature: -40°C to 57°C

Housing Material: Lexan 940 Polycarbonate Plastic

Mount: Surface, Wall or DIN Rail

Password Protection: Yes @ Setup (Base 64 Encoding, 10 Characters)

Connectors: 3-position Removable (Relay- C, NO, NC), 5-position Removable (Power/Input), 8-pin RJ-45 (Network)

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics GAU-ANC-48-160W-LED High Bay LED Fixture is a connected lighting solution for industrial buildings and general areas. Modbus TCP/IP capable, this low profile, highly efficient LED light fixture is a direct replacement for existing four lamp T5HO fixtures, providing twice the lamp life, increased durability, and less energy consumption. Operators can setup remote access, controls and configurations using the Modbus TCP/IP network controller (via a standard web browser).

The GAU-ANC-48-160W-LED integrated 160 Watt LED light fixture is a low profile linear light fixture that provides 19,200 lumens of bright light in a 160° wide flood beam spread. Special heat dissipating design in conjunction with LED technology helps this fixture to achieve an excellent 60,000 hour rated lifespan with 80% lumen retention. The GAU-ANC-48-160W-LED is housed in aluminum casing and the LED assembly is protected by a shatter resistant polycarbonate lens. This unit is multi voltage, operating on 110-277 AC 50/60 Hz, and supplied with a 10` line-in cable with flying leads. We also offer a low voltage 12-24V AC/DC model for low voltage applications, such as off the grid and remote locations powered by alternative energy.

Aevum Network Controlled Lighting Solution: The Aevum Network Controlled Lighting Solution from Larson Electronics enables connected and intelligent illumination using cutting-edge and existing networks. Using Modbus TCP/IP or DALI (for fixtures with dimming features), businesses can seamlessly control lights and sensors from remote locations, without traditional light switches. Web-based panels facilitate real-time monitoring of connected equipment and allows operators to switch units on/off, configure activation settings and more. Businesses may utilize their own systems and software with these controllers, ensuring robust flexibility and cost savings (no contracts). The Aevum Network Controlled Lighting Solution can improve productivity in the workplace by automating basic lighting controls and making lighting controls widely accessible in the facility, via local networks or the internet. Operators also have the option to monitor the status of fixtures from a remote location, which can improve maintenance and reduce downtimes.

Controls: Controls for the LED fixture is accessible using a web-based control panel. Compatible with HTTP, XML, or Modbus TCP/IP protocols, network configuration is accessible using web-based pages (no programming required). Operators can monitor or setup controls from a remote area using the internet or local IP network and any standard web browser. Functions and controls include: on/off, pulse and monitor. LED indicator lights on the device provide the real-time information about digital input voltage, relay coil, network status and network activity. Password protection for the setup page is available (10 characters maximum).



Click Photo to Enlarge

Click Photo to Enlarge



Click Photo to Enlarge

We have eliminated the ballast box normally associated with fluorescent fixtures which reduces overall weight and creates a slimmer unit profile. There is no ballast in this unit and the integrated LED assembly has a 50,000+ hour service life, both of which result in extreme efficiency and greatly reduced maintenance costs. The solid state design of LED technology give this fixture superior resistance to damage from vibration, extremes in temperature, and a lamp life over twice that of standard fluorescent bulbs.

The integrated heat sink allows for efficient heat dissipation, preventing the LEDs from overheating and keeping the overall temperature of the fixture relatively low. Solid state LED technology eliminates the need for a ballast box and lamps, a cumbersome feature of fluorescent fixtures that add weight and require frequent repairs. This low profile light fixture features two adjustable brackets, providing operators with easy installation and allowing for adjustments of the light assembly.

Network: The network controller is equipped with one optically-isolated digital input and one SPDT relay contact. Compatible with 9-28V DC, the unit features a 3-position removable relay (N, NO, NC), a 5-position removable power/inputs and an 8-pin RJ-45 port for network connections. Operators can mount the device on walls, surfaces or din rails for space-saving benefits.

Click Photo to Enlarge

This unit is designed to be either surface mounted or hung from cable or chain and includes built in mounts. The GAU-ANC-48-160W-LED light fixture is ideal for indoor-outdoor applications and suitable for use as general area lighting, shop lighting, work space lighting, garage and warehouse lighting, and anywhere a dependable and low maintenance fixture with high output and efficiency is needed. This light comes with a multi-purpose mounting bracket that can be used for a direct surface mount or reversed and used for chain hanging the unit.

Suggested Applications: Modbus TCP/IP lighting networks, remote lighting networks, warehouses, industrial buildings, general areas, manufacturing floors, commercial offices, garages, lobbies, schools, activity centers, government buildings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-ANC-48-160W-LED

Product ID: 153690

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GAU-ANC-48-160W-LED-Voltage-Mount

Example: GAU-ANC-48-160W-LED-1227-SFC

Voltage	
120/277V	-1227
347-480V	-480V
24V	-24

Mount	
SURFACE	-SFC
CABLE	-CAB

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map