

WCDE-4-2X150LTL-LED

6,000 Watt Generator - Water Cooled Diesel Engine - 25' Telescoping Tower - (2) 150W LED

Fixtures

Product ID: 153693

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

WCDE-4-2X150LTL-LED Mobile Light Tower

Genset Specs:

Engine: Kubota Z482 EPA Tier 4
Engine Type: Vertical, liquid-cooled, 4-cycle diesel engine
Engine Speed: 3600 RPM
No. of Cylinders: 2
Generator: Sincro EK 2 MCT
Voltage: 120V Single Phase
Auxiliary Power Supplies): 120V Duplex Receptacle
Battery 12V
Fuel Cell Capacity: 28 Gallons
Fuel Delivery: Electric
Noise Level: Db level 73 @ 23 ft

Protection

6.8KW Kubota Genset
28 Gallon Fuel Cell
Up to 50+ Hour Continuous Operation
External Grounding
Low Oil, High Engine Temp Auto Shut-Off
Hour Meter - Alternator Warning
High Output MH Lamps
Extreme Area Coverage
40,500 Total Lumen Output
Independently Adjustable Light Heads
Individual Light Switch Circuit Breakers
Dial-in Adjustability per light head
110 Lumens Per Watt Efficiency
Steel Trailer w/ Industrial Grade Paint Finish
Four Point Outrigger System
Withstands 50Mph Winds at Full Extension

Light Mast Specs:

Mast Type: Manual Crank-Up
Boom Height: Up to 25'
Materials: Galvanized Steel
Operation: Manual Hand Crank Winch
Winch: (1) 2500lb, Self-Braking
Stages: Five

Light Specs:

Lamp Type: LED
Lamp Qty: 2
Total Watts: 300 (150W per lamp)
Total Lumens: 40,500 (20,250 per lamp)
Luminous Efficacy: 135 lm/w
Color Temperature: Cool White - 5500-6500K
Lamp Life Expectancy: 80,000 hours
Mounting: Trunnion Mount U-Bracket
Materials: Die Cast Aluminum Housing, OMMA Optics
Housing Color: Natural Aluminum
Coverage: 6 to 7 Acres

Trailer Specs

Materials: Plastic Enclosure, 12ga Formed Steel Chassis
Hitch: 2" Ball Coupler and 3" Pintle Hitch
Finish: Industrial Grade Paint
Axle: (1) 2,000 lbs
Suspension: 2,000 lbs Double Eye Leaf Springs
Outriggers: (4) Adjustable Outriggers w/ 2,500 lbs Manual Leveling Jacks
Lighting: DOT Approved tail, side, brake, and directional lights
Wheels: (2) 13" 5x4.5 Steel Rims
Tires: ST175/80/D13

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in Texas

The WCDE-4-2X150LTL-LED mobile light tower from Larson Electronics is a towable lighting package powered by a water cooled diesel engine turning a single bearing 7,500 watt generator. With two 150 watt LED lamps producing 40,500 total lumens this unit will illuminate a 6-7 acre area continuously without refueling for up to 50 hours.

The WCDE-4-2X150LTL-LED mobile light tower is a self contained towable light tower package that produces enough light to illuminate an area up to 7 acres in size. This unit contains a water cooled diesel engine powering a 7,500 watt generator, which supplies the current to two 150 watt LED lamps producing 20,250 lumens each for a combined total of 40,500 lumens of light. This unit can run uninterrupted for 50 hours straight without refueling and includes a telescoping light mast which can elevate the two LED lamps to a height of 25 feet. This mobile floodlight package is ideal for emergency services, large scale event illumination, construction, mining, industrial operations and anywhere an extended operation capable mobile lighting solution is needed.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

The WCDE-4-2X150LTL-LED mobile light tower incorporates a long list of impressive features. The diesel engine is a water cooled Kubota that operates at 3600 rpm. This engine features key operated electric starting, a full twelve volt electrical system,

automatic low oil pressure and high temperature safety shutoffs, dual fuel filters and easy access oil and radiator drain ports to facilitate maintenance. A 28 gallon fuel tank allows the engine to operate for 50 hours continuously without refueling. The 7,500 watt generator is a single bearing design and produces 120/240 volt current at 60 Hz. The generator uses a four wire hookup system with an external ground allowing for setting up both electrical and mechanical safe grounding systems.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

Lights: The lighting system on this unit is comprised of two 150 watt LED lamps producing 20,250 lumens of light each attached to the end of the telescoping light boom. These lights draw only 150 watts at 1.25 amps from a 120 volt electrical system. Each lamp features Sixteen CREE® high output LEDs producing 1,350 lumens each are arranged in rows and paired with PMMA high purity optics to produce a well focused 24° wide spot beam that is ideal for providing far reaching concentrated illumination while still covering a substantial amount of area. Each floodlight is securely fastened to the light boom and each lamp includes a support bracket to help maintain lamp stability within its housing. The lamps are connected to the power source via a water tight male pin connector that attaches to a receptacle located on the end of the telescoping boom.



[Click Photo to Enlarge](#)

Controls: The operations system for this unit is a centrally located control panel within the light tower enclosure. Two circuit breaker protected switches allow individual control of the lights while an individual hour meter tracks unit operating time. Also included is an alternator warning light, fuel primer system, preheating switch, and a 120 volt GFCI duplex receptacle for auxiliary power takeoff.

Telescoping Boom: The telescoping boom consists of five sections extending up to 25 feet through the use of a manual self braking winch and allows for rotating the lights 360 degrees. The telescoping boom is constructed of galvanized steel to resist rusting and corrosion and is capable of withstanding 50 mph winds when extended to its full height and the stabilizing outriggers are deployed. The stabilizing outriggers are a four point design with one located under the trailer tongue, two on the sides and one on the back of the unit. The two side outriggers are adjustable and include 1,000 lbs swivel jacks for leveling and stabilizing the tower.

Housing: All of the operating components are housed within a protective compartment constructed of 14 gauge steel and designed to provide airflow for cooling. A spillage free frame with an external drain system will contain all fluids to prevent road hazards or damage to the environment. Side wing doors provide access to the interior while latches provide secure closing when the unit is in use. The design and construction of this enclosure along with the commercial grade muffler system helps this unit operate at a low 73 Db noise level @ 23 ft. The entire unit can be loaded and unloaded onto trucks via forklift sleeves mounted to the top section of the light mast. The entire unit is mounted onto a two wheel trailer with a 2,000 lbs leaf spring axle. A standard two

inch ball coupling and two standard safety chains allow for easy hookup and towing.

Frequently Asked Questions (FAQ)

WCDE-4-2X150LTL-LED

Product ID: 153693

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

WCDE-4-2X150LTL-LED-Beam Config

Example: WCDE-4-2X150LTL-LED-10SP

Beam Config	
10° SPOT	-10SP
25° WIDE SPOT	-25WS
40° NARROW FLOOD	-40NF
60° FLOOD	-60F
90° WIDE FLOOD	-90WF

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)