Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXC-100-12.3-20A-L6.20

100' 12/3 SOOW Extension Power Cord - 250V - 20A Rated, Outdoor Rated - L6-20P, L6-20C

Product ID: 154016

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXC-100-12.3-20A-L6.20 - 100` 12/3 SOOW 20A Extension Cord

Male Cord Cap: 20A L6-20P [250V]
Female Connector: 20A L6-20C [250V]
Voltage Rating: 250V
Max Amp Rating: 20A
Cable Type: 12/3 SOOW
Cable Length: 100`
Weight: -

Summary

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The EXC-100-12.3-20A-L6.20 from Larson Electronics is a 100 foot 12/3 SOOW Extension Power Cord that is designed for heavy duty and outdoor applications. This rugged extension cord is constructed of 12-gauge 3-conductor wire, equipped with a 20-amp rated male cord cap and 20-amp female connector, and allows operators to extend power to equipment when stationary outlets are not readily available.

The EXC-100-12.3-20A-L6.20 provides a safe and effective way for operators to extend power to a variety of devices for plant maintenance, power generators, construction and other temporary applications. This unit operates on 250V AC and features a 100-foot 12/3 SOOW cord with a 20-amp rating. The input side of the extension cord contains a 20-amp 250V L6-20P male cord cap; and the output side is equipped with a 20-amp 250V L6-20C female connector.

Applications: This accessory is ideal for indoor or outdoor use and applications

including but not limited to, generators, construction sites, plant maintenance, plant turnarounds, shows, exhibits, industrial equipment, uninterruptible power supplies (UPS battery backups), stage equipment, and shipyard operations. These industrial extensor cords are popularly used in applications where external power sources are often necessary. We also offer class rated extension cords for use within explosion proof and hazardous location environments.
Larson Electronics is a manufacturer and as such can build extension cords and portable transformer systems to your specifications. Although we carry several models of power distribution transformers, we can deliver custom ordered units almost as quickly as our prebuilt units If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





EXC-100-12.3-20A-L6.20

Product ID: 154016

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**