

EXHL-PM-RPS-17AH-LE1-XMB

12W Rechargeable Explosion Proof LED Light - C1D1-2, C2D1-2 - Aluminum Frame - Magnetic Bracket

Product ID: 154175

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXHL-PM-RPS-17AH-LE1-XMB Explosion Proof LED Light Fixture

Lamp Type: LED

Dimensions: 8"L x 6"W x 14"H - Lamp

Weight: -

Voltage: Rechargeable/Battery Powered Unit

Watts: 12W

Lumens: 1,320

Luminous Efficacy: 110 Lm/W

LED Light Color: 6000K - White

LED Life Expectancy: 50,000 hours

Lighting Configuration: 10° Spot or 40° Flood

Spot Beam: 800`L x 140`W

Flood Beam: 300`L x 225`W

Ambient Operating Temp Range: -40°C to +60°C

Housing Material: Aluminum

Lens Material: Polycarbonate

Mounting: Portable A-frame w/ Magnetic Hanging Bracket

Battery Runtime: 1.5 Hrs

Charger: AC Charger w/ Connector

Ratings/Approvals

Listed for United States, Canada, Europe, Asia

Class I, Div. 1 & 2, Groups B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Div. 1 & 2, Groups E, F, G

Class III, Div. 1 & 2

NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)

ATEX Ex II 2 G / D

IECEX db IIC Gb

IECEX tb IIC Db IP66

Rechargeable LED Light

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in Texas

The EXHL-PM-RPS-17AH-LE1-XMB from Larson Electronics is a Rechargeable Explosion Proof LED Fixture that produces 1,320 lumens while drawing only 12 watts. The EXHL-PM-RPS-17AH-LE1-XMB is Class I, Divisions 1 & 2, Groups B, C, D, Class I, Zones 1 & 2, Groups IIB+H2, IIA, Class II, Divisions 1 & 2, Groups E, F, G and Class III Divisions 1 & 2 rated for hazardous areas and is listed for use worldwide including the United States, Canada, Europe and Asia. This battery-powered LED light fixture provides up to 1.5 hours of use and superior illumination in hazardous work sites.

The EXHL-PM-RPS-17AH-LE1-XMB produces 1,320 lumens of high-intensity LED light for illumination within hazardous areas and potentially explosive work environments. This explosion proof LED light fixture is battery powered and rechargeable, offering a runtime of 1.5 hours in a fully charged state. The EXHL-PM-RPS-17AH-LE1-XMB is available in two lighting configurations; spot and flood. The spot configuration features a 10° beam that measures 800` L and 140` W. The flood configuration throws a 40° beam that measures 300` L and 225` W. This portable unit is designed for handheld applications, capable of either being carried, like a compact lantern, or used hands-free, as a standalone light.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Durability: The EXHL-PM-RPS-17AH-LE1-XMB explosion proof LED light fixture from Larson Electronics is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining lightweight and easy to use. These units can operate in temperatures of -40° Celsius to 60° Celsius, are waterproof to 3 meters and resist the ingress of dust, dirt and humidity. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations.

Battery: This unit is powered by a rechargeable battery. In a fully charged state, the power cell offers 1.5 hours of runtime. Operators can charge the battery using an AC charger (with an appropriate connector) that plugs into mainstream power

outside of the hazardous area. A heavy-duty SOOW cord connects the bottom and top enclosure and facilitates electrical connections.

Mounting: This explosion proof LED light fixture is supported by a sturdy aluminum A-frame, which connects the top enclosure (LED lamp and power button) with the bottom enclosure (batteries and disconnect for charging cord). The top enclosure features a magnetic hanging bracket mount for seamless attachment to compatible metallic surfaces, such as magnetic shelves, walls, cabinet doors, work stations and more. To secure the LED lamp, operators simply attach the back of the magnetic hanging bracket component on the desired surface. After use, the unit can be removed quickly, without tools. Robust positioning of the beam is facilitated by adjusting a bracket on both sides of the LED light head, which can be re-tightened to hold the luminary in position. A single thru-hole mounting bolt allows operators to adjust the rotation of the fixture by loosening one bolt.

Applications: Hazardous locations, inspections, detailed tasks, petroleum refineries, chemical and petrochemical plants, paint spray booths, food manufacturing buildings, grain storage sites, woodshops, automotive garages and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

EXHL-PM-RPS-17AH-LE1-XMB

Product ID: 154175

Export Control Classification Number (ECCN): EAR99

Options:

EXHL-PM-RPS-17AH-LE1-XMB-Beam Config

Example: EXHL-PM-RPS-17AH-LE1-XMB-SP

Beam Config	
SPOT	-SP
FLOOD	-FL

Links (Click on the below items to view):

- [HigResPic1](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)