Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EYM-3.5

Explosion Proof Sealing Fitting - Class I, II, III - Aluminum - 3.5" NPT Hub - Gray

Product ID: 154341

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EYM-3.5 Sealing Fitting

Unit Type: Explosion Proof Sealing Fitting
Dimensions: 7.25" x 8.5" x 8.5"
Weight: 17.2 lbs
Turn Radius: 4.75”
Materials: Aluminum
Finish: Powder Epoxy Paint
Hub Size: 3.5" NPT
Color: Gray

Ratings

Class I, Divisions 1&2 Groups C,D
Class I, Zones 1&2 Groups IIB,IIA
Class II, Divisions 1&2 Groups E,F,G
Class III

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Larson Electronics EYM-3.5 Explosion Proof Sealing Fitting provides tight and secure electrical installations in combustible sites and industrial facilities. Constructed of aluminum, the accessory comes with a turn radius of 4.75" and a 3.5" NPT hub.

The EYM-3.5 ensures tight seals and prevents the passage of combustible substances in electrical systems installed in flammable environments. This accessory features a turn radius of 4.75". Constructed of aluminum with a powder epoxy paint finish, the explosion proof sealing fitting is suitable for use in Class I,

II, III and Class I, Zones 1 & 2 environments.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364






CLASS I II
GRP. C,D,E,F,G

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



EYM-3.5

Product ID: 154341

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**