
Golight Radioray Portable Remote Controlled Spot/Flood Light w/ Wired Remote Control & Cigarette Plu

GL-5167-F



GL-5167-F Golight Radioray

Lamp Type: 65 Watt Halogen Bulb

Dimensions: 6" W x 6" Depth x 8" H

Weight: 5 Lbs

Total Watts: 65 watts

Voltage: 12V DC

Lighting Configuration: Spotlight and Floodlight Combo

Amps: 5.5 Amps

Mounting: Permanent Mount Shoe Base with Suction Cup

Total Lumen: 1,300

Lamp Color Temperature: 6000 Kelvin

Weather Rating: Weatherproof

Movement Range: 135° Tilt - 370° Rotation

Remote Control: Single Wired Hand Held Remote

Warranty: 3 Years

Summary/Certifications

65 Watt, 1,300 Lumen

12 VDC Operation

Meets Marine Standards for Fresh / Saltwater Use.

UV and Weatherproof

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-498-3363

E-mail: sales@larsonelectronics.com

3 Year Limited Warranty

The GL-5167-F Golight Radioray from Larson Electronics is a 65 Watt motorized spot and flood light combo that operates with a hand held wired remote control. This particular model is available in white and has a removable permanent mount shoe base. It produces a wide spot beam with an effective working beam of 700 feet and has a 5 million candlepower rating.

The GL-5167-F Golight Radioray is designed for use in all weather conditions and produces 1,300 lumen of intense light output. These units feature remote control operation that allows users to rotate the light 370 degrees with a hard stop and to adjust vertical tilt through 135 degrees. Remote operation is provided by one hand held wired remote controller that is connected to the remote through a wiring harness.

Remote Operation: Remote control functions include on/off, and 4 buttons which control up, down, left and right movement. The light will continue movement as

long as the buttons are pressed. Releasing the buttons stops movement and holds the Golight in position. A fast and slow mode button (turtle/hare) controls the speed of the motor while the pan and tilt function buttons are depressed. Holding the button for 12 seconds in fast mode results in a full 370 degree rotation, and 8 seconds for full tilt. Slow mode is used for pinpoint accuracy at distance and is approximately 35 seconds for full rotation and 20 seconds for one full range of tilt. Remotes are 3 inches long by 2 inches wide by 3/8 inch thick.

Durability: The GL-5167-F Golight Radioray is designed for hunting and demanding outdoor use with a weather resistant housing constructed of high quality ASA Luran thermoplastic that is heat resistant, impact resistant, UV resistant and able to withstand rugged use and abusive conditions. This particular Golight is white in color, making it ideal for docks and buildings where an attractive appearance is desired. Remote movement of this spotlight is provided by an automotive grade internal motor, gear, and transmission assembly that is constructed of LEXAN, brass, and stainless steel to provide rust and corrosion resistance as well as long life and reliable operation.

Mounting: The light slides on and off the base of the light. When the shoe is installed, a spring loaded button pops up locking the light into the base. The shoe base completely encapsulates the suction cup base. When the base is removed, the light can be mounted using the suction cup and the locking lever on the side to activate suction mount. The suction cup mount is released via side mount lever. The suction cup is not suitable for moving vehicles, boats, etc. The shoe has four predrilled holes for permanent mounting.

Power: This light operates with 12 volts DC and draws 5.5 amps, making it ideal for vehicles, boats, ATVs, and similar sources of 12 volt direct current. On this particular model, the light has a 16 foot cord that ends in a cigarette plug. The cord runs from the Golight, to the remote control and then ends in the cigarette plug.

Light Output: The lamp in this Golight Radioray is a 65 watt Halogen Cr5 Pentabeam II bulb which produces 1,300 lumen. This bulb is paired with a tight focus spot beam optics to produce a spot beam 700 feet in length. This lamp has a 6000K color temperature, giving it very good color rendering and contrasting properties and the ability to clearly and sharply illuminate objects at long distances. This beam is effective to the far end of its reach, producing enough illumination to read a book at 700 feet.

New Flood Design: With a new flood design, the GL-5167-F can now swap it's output from a flood to a spot beam in a matter of seconds. The GL-5167-F has undergone a change to its bulb, lens, as well as frame with two brackets for receiving lock-in tabs. Two tabs lock the flood lens into place to create a beam 120` L x 100` W. Previous flood models emitted a beam 60` L x 50` W. When lens is snapped off and a clear, spot lens is revealed, the GL-5167-F then emits a beam 750` L x 250` W at it`s farthest point.

This high power Golight Radioray is ideal for hunting, security, boating, law enforcement, emergency services, utilities, and anywhere high power and remote control functionality are desired.

[Click Here to Compare Golight Models](#)

Golight Radioray Features

1. Weather Proof Lamp and Remote Control
2. Remote Control Programmable with More than 60,000 Possible Channels. Remotes Can be Programmed to Control One Golight or Several
3. R.F. Frequency, F.C.C., S.A.E. tested and Canada Certified
4. Remote Control Range up to 100 Feet
5. Automotive Grade 12 Volt D.C. High Torque Motor
6. Weatherproof Connectors Meet OEM Vehicle Manufacturer Specifications
7. Meets Marine Standards for Fresh Water and Saltwater Use
8. 1,300 Lumen, 700 Foot Beam Length
9. 12 Volt DC 5.5 amps Draw

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- [Addpic1large](#)
- [DimensionalDrawing](#)
- [large](#)
- [Manual](#)
- [medium](#)
- [SpecSheet](#)
- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [Video1](#)