

WAL-C-2XM

Portable Light Tower - 2 X 1000 Watt Metal Halide Lights- Covers 98,000 SF - Extends to 14 feet

Product ID: 1632

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

WAL-C-2XM QuadPod Light Tower

Lamp Type: (2) Metal Halide

Lighting Configuration: Flood Pattern

Dimensions: Adjustable Tower 7 to 14 Feet Height

Total Watts: 2200 Watts

Total Lumens: 220,000

Voltage: Multi-Tap: 120V AC, 220V AC, 240V AC or 277V AC

Amps: 9 Amps @ 240V AC Voltage

Wiring: 25 Feet SOOW Cord w/ General Area Cord Cap

Cord Cap Options: 6-15 Straight, L6-15 Twist, L5-30P Twist, L6-30P Twist, L7-15P, L7-20P, L7-30P, UK BS1363, Intl. Schuko or Pigtail

Mounting: Steel Square Tube Quadpod, 7-14' Adjustable Height

Weight: Tower only 33 lbs, Total 175 Lbs

Quick Summary

2,200 Watt, 220,000 Lumen Light Assembly

98,000 Square Foot Coverage

Adjustable Tower 7 - 14 Feet

Wheeled

25 Foot Cord

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)









WAL-C-2XM

Product ID: 1632

Export Control Classification Number (ECCN): EAR99

Options:

WAL-C-2XM-Voltage-Cord Cap

Example: WAL-C-2XM-120V.60-6.15

Voltage	
120V 60HZ	-120V.60
220V 60 HZ	-220V.60
240V 60HZ	-240V.60
277V 60HZ	-277V.60

Cord Cap	
6-15 STRAIGHT	-6.15
5-20 STRAIGHT	-5.20
6-20 STRAIGHT	-6.20
L6-15 TWIST	-L6.15
L5-20 TWIST	-L5.20
L6-20 TWIST	-L6.20
L5-30 TWIST	-L5.30
L6-30 TWIST	-L6.30
L7-15 TWIST	-L7.15
L7-20 TWIST	-L7.20
L7-30 TWIST	-L7.30
UK BS1363	-BS1363
INTL SCHUKO	-SCHUKO
PIGTAIL	-PIGTAIL

Links (Click on the below items to view):

- [Beam Information \(Coverage, Datafile\)](#)
- [IES \(Photometric File\)](#)
- [Photometric Flood Report](#)
- [Photometric Indoor Report](#)
- [Photometric Polar Graph](#)
- [Photometric Road Report](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)