

EPL-FL1524-25

Explosion Proof Fluorescent Handheld Light - Class 1 Division 1 and Class II Division 1

Product ID: 2001

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-FL1524-25 Work Light

Listing: United States

Dimensions: 27"-L x 3.25"-Dia

Weight: 14.5 lbs

Voltage: 120-277 Volts 50/60 Hz or 11-25 Volts AC/DC

Total Watts: 15 watts

Lumens: 700

Luminous Efficacy :46.67 lm/w

Lamp Life: 50,000+ Hours

Lamp Color: 4,100K

CRI: >75 White

Power Efficiency: >95%

Power Factor: 0.992

Lamp Lengths: 2 Foot

Amperage: 0.13 amps @ 120V, 0.07 amps @ 240V, 0.05 amps @ 277V

Material: Rubber / Copper Free Aluminum

Mounting: Handheld / Aluminum Hook

Wiring: 25` 16/3 AWG SOOW Cable

Cord Cap: 5-15, 6-15, L5-15, L6-15, BS1363, Schuko, or Pigtail

F.M. Approval: [U.S Certificate](#)

Ratings/Approvals

Class 1, Division 1 & 2 for Group D

Class II, Division 1 Groups E, F, G

Class III, Division 1 & 2

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)









EPL-FL1524-25

Product ID: 2001

Warranty: 36 Months

Harmonized System (HS) Code: 85131000

Export Control Classification Number (ECCN): EAR99

Options:

EPL-FL1524-25-Voltage-Cord Cap

Example: EPL-FL1524-25-1227-5.15

Voltage	
120-277V AC	-1227
11-25V AC/DC	-1224

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UK BS1363	-BS1363
INTL SCHUKO	-Schuko
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [DXF \(2D CAD Model\)](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [SpecSheetArabic](#)
- [SpecSheetFrench](#)
- [SpecSheetSpanish](#)
- [STEP File \(3D CAD Model\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [Video1](#)
- [Video2](#)
- [Video3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)