

### **TPM-2XWP60E-DNS-10C**

**120W LED Light w/ Telescoping Pole Mount - Adjustable 3' to 8.5' - Day/Night Sensor - 120-277VAC**

**Product ID: 221516**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

---

#### **TPM-2XWP60E-DNS-10C Telescoping Industrial LED Light**

**Lamp Type:** CREE LED

**Lamp Dimensions:** W-9" D-3.25" H-6.5"

**Pole Dimensions:** Telescoping - 3' to 8.5' Adjustable

**Weight:** 8.3 Lbs Per Lamp

**Total Watts:** 120W (60 Per Lamp)

**Voltage:** 120-277V AC 50/60 Hz

**Lumens:** 10,800 (5,400 Per Lamp)

**LED Life Expectancy:** 50,000 Hours

**CRI:** 80

**Amps:** 1 @ 120 VAC

**Light Color:** 5,600K

**Beam Type:** 60° Flood

**Mounting:** Adjustable U-Bracket w/ Thru-Holes

**Housing Materials:** Cast Aluminum

**Housing Finish:** Powder Coated

**Lens Materials:** Polycarbonate

**Ambient Temp Range:** -25°C to +60°

**Luminous Efficacy:** 90 lm/w

**Wiring:** 10' 16/3 SOOW Cord w/ General Area Cord Cap

**Cord Cap Options:** 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist, UK BS1363, Intl. Schuko, Pigtail

#### **Quick Summary**

Listed for use in United States and Canada

Waterproof/Vapor Proof

3' to 8.5' Adjustable Pole

Universal Voltage 120-277V

IP68 Waterproof

Impact/Vibration Resistant Construction

50,000 Hour LED Life

ETL Approved for Wet Locations

Day/Night Photocell

#### **Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.498.3364

---

---

## Frequently Asked Questions (FAQ)



**TPM-2XWP60E-DNS-10C**

**Product ID: 221516**

**Export Control Classification Number (ECCN): EAR99**

**Options:**

**TPM-2XWP60E-DNS-10C-Cord Cap**

**Example: TPM-2XWP60E-DNS-10C-5.15**

| Cord Cap      |          |
|---------------|----------|
| 5-15 STRAIGHT | -5.15    |
| 6-15 STRAIGHT | -6.15    |
| L5-15 TWIST   | -L5.15   |
| L6-15 TWIST   | -L6.15   |
| UK BS1363     | -BS1363  |
| INTL. SCHUKO  | -Schuko  |
| PIGTAIL       | -Pigtail |

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)