

ATEX-HALP-24-2L-T8-2X18W-R1-220V

36W Flameproof Fluorescent Linear Fixture - 220V, 50Hz - (2) 2' T8 Lamps - ATEX/IECEEx - IP66

Product ID: 222230

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-HALP-24-2L-T8-2X18W-R1-220V Flameproof Fluorescent Light

Listing: International, European Union

Lamp Technology: Fluorescent

Dimensions: 28.5" x 8.7" x 5.7" (725mm x 222mm x 145mm)

Lamp Quantity: 2

Weight: 11.02 lbs (5 kgs)

Voltage: 220V AC

Frequency: 50 Hz

Total Watts: 36W (2 x 18W)

Total Lumens: 2,380 lms (2 x 1,190 lms)

Luminous Efficacy: -

Lamp Life: 7,500+ Hours

Color Temperature: 5000K, 4100K or 2700K

Color Rendering Index: 75

Lamp Type: T8

Lamp Base: 2-pin G13

Replacement Lamp: -

Beam Angle: -

Lighting Configuration: Flood Pattern

Power Efficiency: -

Power Factor: >0.98

Ballast Type: Electronic

Ballast Position: Internal

Ratings/Approvals

ATEX/IECEEx Rated

Zone 1/Zone 2

Zone 21/Zone 22

Ex deq IIC T4 Gb

Ex deqmb IIC T4 Gb

Ex II 2GD Ex deq IIC T4 Gb

Ex II 2GD Ex deqmb IIC T4 Gb

IP66

Amperage: 0.2A @ 220V

Ambient Operating Temp Range: -25°C to +40°C

Operating Temp Rating: T4

Housing Material: Glass Fiber Reinforced Polyester

Housing Finish: -

Lens Material: Polycarbonate

Gasket Material: Foam

Mount: -

Terminals: L1, N + (2) PE - 0.39" (10mm)

Hub Quantity: 1

Hub Size/Location: (1) 1.5" (M25) @ Side

Stopping Plugs: (2) 1.5" (M25) Molded Plastic/Polyamide

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics ATEX-HALP-24-2L-T8-2X18W-R1-220V Flameproof Fluorescent Linear Fixture is designed for outdoor illumination in ATEX/IECEx rated flammable environments. Equipped with two, 2-foot T8 fluorescent lamps, this 36-watt fixture is compatible with 220V AC, 50 Hz. The IP66-rated unit is constructed of glass fiber reinforced polyester with a polycarbonate lens and features an internal electronic ballast with an interlocking system for protection.

The ATEX-HALP-24-2L-T8-2X18W-R1-220V is a powerful lighting solution for combustible facilities, industrial sites and outdoor locations. This 36-watt unit operates on 220V AC, 50 Hz and contains two, 2-foot T8 fluorescent lamps (2-pin G13 base). During use, the fixture offers 2,380 lumens of output in a flood beam configuration, with an exceptional CRI rating of 75. Color temperature options include: 5000K, 4100K or 2700K.

An electronic, internal ballast ensures reliable lighting performance and features an interlock switch that disconnects all poles to the ballast, as well as turns the power off when the diffuser is opened.

This full-plastic explosion proof fixture is constructed of glass fiber reinforced polyester. The lens consists of UV-resistant polycarbonate and is equipped with a foam gasket. This IP66-rated unit comes with an approximate lifespan of 7,500+ hours and is suitable for ATEX/IECEx rated Zone 1/Zone 2 and Zone 21/Zone 22 flammable environments. Equipped with a T4 temperature rating, the outdoor fixture can be used in locations with ambient temperatures ranging between -25°C to +40°C.

Wiring: The ATEX-HALP-24-2L-T8-2X18W-R1-220V features L1, N and two PE terminals for completing electrical connections. Cables are fed through one, 1.5" (M25) hub, located at the side of the fixture. This unit comes with two, 1.5" (M25) molded plastic/polyamide stopping plugs. A central locking system protects the internal components of the unit, which must be unlocked during installation or relamping.

Mounting Compatibility: This explosion proof light is compatible with the following mounting configurations (not included): ceiling, pendant, chain hanging, angle bracket, pole clamp oil derrick and pole top. We offer these mounting accessories at an additional cost.

Suggested Applications: Paint spray booths, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, gas processing plants, chemical manufacturing, waste water treatment plants, offshore applications and more. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)









ATEX-HALP-24-2L-T8-2X18W-R1-220V

Product ID: 222230

Export Control Classification Number (ECCN): EAR99

Options:

ATEX-HALP-24-2L-T8-2X18W-R1-220V-Color Temp

Example: ATEX-HALP-24-2L-T8-2X18W-R1-220V-50K

Color Temp	
5000K	-50K
4100K	-41K
2700K	-27K

Links (Click on the below items to view):

- [ATEX Certificate \(European Explosion Proof\)](#)
- [Certificate 1, Misc](#)
- [Dimensional Drawing 2D](#)
- [IEC Ex Certificate \(International Explosion Proof\)](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [STEP File \(3D CAD Model\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)