

EXP-MS-N4X-AT-HV-V5

400W Explosion Proof Motion Sensor - 10-20' Mounting - 15'x15' Area Coverage - 170 Minute Adj Timer

Product ID: 222236

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EXP-MS-N4X-AT-HV-V5

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-MS-N4X-AT-HV-V5 Explosion Proof Adjustable Motion Sensor

Listing: NRTL Listed for United States, Canada and IECEx/ATEX Rated

Dimensions: 7"-W x 5"-H x 9"-D

Detection: Motion

Detection Coverage: 15' x 15' (Mounted @ 16')

Tilt Angles: -90° to +30° - Elevation

Reach: 6.5' to 32' - Adjustable

System Voltage: 120V, 208V, 220V, 240V or 277V AC

Maximum Wattage: 400W

Output Hold Time: 170 Mins (Adjustable)

Mains Frequency: 50/60 Hz

Ambient Temperature Range: -22°F to +140°F

Radiated Frequency: 5.8 GHz

Operation: Normally Opened or Normally Closed

Wiring: Flying Leads

The Larson Electronics EXP-MS-N4X-AT-HV-V5 Explosion Proof motion sensor is approved Class I Divisions 1 & 2 and Class II Divisions 1 & 2 and the ability to power lights or other equipment within hazardous locations based on motion. This C1D1 rated motion sensor features adjustable sensitivity and time delay after motion. Equipped with an adjustable timer, the EXP-MS-N4X-AT-HV-V5 can handle a maximum load of 400 watts.

This explosion proof motion sensor is ideal for operators seeking a high quality explosion proof motion sensor rated for use in hazardous areas designated Class I Divisions 1 and Class II Division 1. This explosion proof motion detector provides up to 15' by 15' coverage when mounted at 16'. The entire unit is constructed of copper free non-sparking aluminum construction with a glass window for motion detection. This unit is easily wall mounted via integral mounting bracket, which can be adjusted -90° to +30° vertically after installation. The explosion proof housing provides two 1/2" or 3/4" hub openings located on either side of the housing for running electrical conductors in a feed through configuration. A bushing seal at each conductor opening prevents damage to wiring insulation.

This unit leverages cutting-edge microwave sensors to detect motion. When in use, the device sends out discreet waves that are reflected back from nearby walls and objects (not heat or light). Microwave sensors are not affected by line of sight, resulting in wider and more accurate coverage of the target area. By comparison, traditional infrared sensors can only detect heat and light (factors used to identify movement) within the unit's field of view. Microwave sensors also provide stable performance in unpredictable climates and can penetrate glass, plastic and other non-metallic objects.

The EXP-MS-N4X-AT-HV-V5 comes with an adjustable timer, which offers an adjustable range of 10 seconds to 170 minutes. When the sensor is engaged, the circuit stays closed, keeping device running for the set duration (between 10 seconds - 170 minutes in 10 second increments). The timer component features a repeating accuracy value of +/- 0.5% and a setting accuracy value of +/- 2%.



EXP-MS-N4X-AT in operation. [Click Here](#) to view our Flex Couplers available for purchase.

[Click Images to Enlarge](#)

Reach Setting: For best results, it is recommended to adjust the motion sensitivity of the unit by configuring the reach setting. Reach is the term used to describe the radius of the circular detection zone produced on the ground. After mounting the sensor at a height of 10-20 feet, operators can adjust each control to- select distance sensitivity. This detection distance is measured using a person who is between 5.2 feet and 5.5 feet tall with an average build, moving at a speed of 1.0-1.5m/sec. If any of these variables are changed, the detection distance will also change.

The EXP-MS-N4X-AT-HV-V5 operates like a standard on/off light switch. The circuit is normally open when no motion is present. Once motion is detected, the internal switch changes to a closed circuit, allowing voltage to pass through the sensor and power the device(s) at the other end.

This unit is designed to operate on 120V, 208V, 220V, 240V, or 277V AC electrical circuits. We also offer low voltage 12-24V AC or DC electrical systems. This motion sensor is suitable for use in environments where combustible dusts and particulates may be present.



Motion Detected Through a Wall

The EXP-MS-N4X-AT-HV-V5 has 1/2" or 3/4" NPT tapped conduit openings on either of the unit in feed through versions while dead end versions have a single conduit hub, providing easy and secure connection to main power line supplies.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Lighting, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Image: EXP-MS-N4X-AT-HV-V5



Image: EXP-MS-N4X-AT-HV-V5



Image: EXP-MS-N4X-AT-HV-V5




Image: EXP-MS-N4X-AT-HV-V5

EXP-MS-N4X-AT-HV-V5

Product ID: 222236

Export Control Classification Number (ECCN): EAR99

Options:

EXP-MS-N4X-AT-HV-V5-Voltage-Contacts-Hub Config

Example: EXP-MS-N4X-AT-HV-V5-120V-NO-0.75IN

Voltage	
120V	-120V
208V	-208V
220V	-220V
240V	-240V
277V	-277V

Contacts	
NORMALLY OPEN	-NO
NORMALLY CLOSED	-NC

Hub Config	
3/4 IN	-0.75IN
1/2 IN	-0.5IN

Links (Click on the below items to view):

- **ATEX Certificate (European Explosion Proof)**(<https://www.larsonelectronics.com/images/product/ATEXCert/222236.PDF>)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(<https://www.larsonelectronics.com/images/product/CECCert/222236.PDF>)
- **CE Certificate**(<https://www.larsonelectronics.com/images/product/CECert/222236.PDF>)
- **Certificate 1, Misc**(<https://www.larsonelectronics.com/images/product/Cert1/222236.PDF>)
- **Certificate 2, Misc**(<https://www.larsonelectronics.com/images/product/Cert2/222236.PDF>)
- **Certificate 3, Misc**(<https://www.larsonelectronics.com/images/product/Cert3/222236.PDF>)
- **Certificate 4, Misc**(<https://www.larsonelectronics.com/images/product/Cert4/222236.PDF>)
- **Dimensional Drawing 2D**(<https://www.larsonelectronics.com/images/product/DimensionalDrawing/222236.PDF>)
- **IEC Ex Certificate (International Explosion Proof)**(<https://www.larsonelectronics.com/images/product/IECExCert/222236.PDF>)
- **MSDS (Material Safety Data Sheet)**(<https://www.larsonelectronics.com/images/product/Msds/222236.PDF>)
- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/222236.PDF>)
- **RoHS Certificate (Restriction of Hazardous Substances)**(<https://www.larsonelectronics.com/images/product/RoHSCert/222236.PDF>)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(<https://www.larsonelectronics.com/images/product/NECCert/222236.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/222236.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/222236.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/222236.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/222236.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/222236.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/222236.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/222236.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/222236.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/222236.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/222236.JPG>)
- **HigResPic10**(<https://www.larsonelectronics.com/images/product/HigResPic10/222236.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)