

MT-ATX-FP-3P-208D-15KVA-240D-N3R

15 kVA Autotransformer - 208V Delta Primary - 240V Delta Secondary - NEMA 3R - Fully Potted
Product ID: 222408

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ATX-FP-3P-208D-15KVA-240D-N3R Fully Potted Autotransformer

Transformer Type: Autotransformer

Phase: Three Phase

Frequency: 60 Hz

kVA: 15

Primary Voltage: 208 V Delta

Taps: -

Secondary Voltage: 240 V Delta

Winding Material: Aluminum

Insulation: 220°C

Temperature Rise: 150°C

Impedance (Std): -

Seismic: Yes

Sound Level: Meets NEMA ST-20 Standards

Primary Termination: -

Secondary Termination: -

Enclosure Material: NEMA Type 3R Heavy Duty Ventilated

Finish: ANSI 61 Grey, UL50 Finish

Dimensions: -

Weight: -

Mounting: Floor or Wall Mount

Ratings

Listed for United States and Canada

ANN Cooling

IP24 Rated

Fully Potted Autotransformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The MT-ATX-FP-3P-208D-15KVA-240D-N3R 208 V Delta 3 Phase Energy Efficient Fully Potted Autotransformer from Larson Electronics is

powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ATX-FP-3P-208D-15KVA-240D-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Transformer Features: With a transformer rating of 15 kVA, the MT-ATX-FP-3P-208D-15KVA-240D-N3R autotransformer is a three phase unit with a primary voltage of 208 V Delta. It also provides a secondary voltage of 240 V Delta. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor or wall mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP24.

Benefits: The MT-ATX-FP-3P-208D-15KVA-240D-N3R autotransformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This autotransformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MT-ATX-FP-3P-208D-15KVA-240D-N3R is an autotransformer which means that it has the ability to adjust the supply voltage to match specific load requirements when load isolation from the supply line is not required. Autotransformers are typically used in distribution systems that require small voltage corrections during operation.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)









MT-ATX-FP-3P-208D-15KVA-240D-N3R

Product ID: 222408

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)