

EPLRL-50-0.5-AR-300PSI

Explosion Proof Air Reel - Class I, II, III - Class I, Zone 1 - 50' Air Travel - 1/2" ID 300 PSI

Product ID: 222492

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLRL-50-0.5-AR-300PSI Explosion Proof Air Reel

Unit Type: Explosion Proof Air Reel

Dimensions: -

Active Air Travel: 50'

Application: Lift/Drag

Guide Arm: 4-Roller 12-Position, Adjustable/Removable

Materials: Powder Coated Steel w/ Zinc-plated Hardware

Compatibility: 1/2" ID 300 PSI

Hose: Included

Ratings

Class I, Division 1, Groups C & D

Class II, Division 1, Groups E, F & G

Class III

Class I, Zone 1 (AEx d IIB, EX d IIB)

NEMA 9, NEMA 4 (IP56)

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The EPLRL-50-0.5-AR-300PSI is an Explosion Proof Air Reel for Class I, Division 1; Class I, Zone 1; Class II, Division 1 and Class III locations. The lift/drag unit offers 50 feet of active air travel and is designed for 1/2" ID 300 PSI. This NEMA rated explosion proof air reel comes with a hose.

*****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE*****

The EPLRL-50-0.5-AR-300PSI is recommended for air-reel applications in combustible environments. Designed for 1/2" ID 300 PSI, this unit provides 50 feet of active air travel and is suitable for lift/drag applications. A 4-roller, 12-position adjustable and removeable guide arm reduces the possibility of tangling

and makes operation seamless. Constructed of powder coated steel with zinc-plated hardware, the explosion proof air reel comes with a hose.



[Click Image to Enlarge](#)



[Click Image to Enlarge](#)



Applications: Manufacturing plants, chemical processing, oil and gas, refineries, industrial pumps, fleet servicing, maintenance and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



EPLRL-50-0.5-AR-300PSI

Product ID: 222492

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)