

**1 kVA Isolation Transformer - 240V Primary - 120V Secondary - NEMA 3R - Fully Potted - 1 Phase**

Part #: MT-ISX-FP-1P-240V-1KVA-120V-N3R



The MT-ISX-FP-1P-240V-1KVA-120V-N3R 240 V 1 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-1P-240V-1KVA-120V-N3R provides increased reliability, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\***

**Transformer Features:** With a transformer rating of 1 kVA, the MT-ISX-FP-1P-240V-1KVA-120V-N3R fully potted isolation transformer is a single phase unit with a primary voltage of 240 V. It also provides a secondary voltage of 120 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be either floor or wall mounted. The unit also features a 180°C insulation with a 115°C temperature rise and is rated IP24.

**Benefits:** The MT-ISX-FP-1P-240V-1KVA-120V-N3R isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

**Safety:** The MT-ISX-FP-1P-240V-1KVA-120V-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-FP-1P-240V-1KVA-120V-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

**Applications:** Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

#### **Specifications / Additional Information**

##### **MT-ISX-FP-1P-240V-1KVA-120V-N3R Isolation Transformer**

**Phase:** Single Phase

**Frequency:** 60 Hz

**kVA:** 1

**Primary Voltage:** 240 V

**Secondary Voltage:** 120 V

**Winding Material:** Copper

**Taps:** None

**Insulation:** 180°C

**Temperature Rise:** 115°C

**Primary Termination:** -

**Secondary Termination:** -

**Sound Level:** 45 dB

##### **Approvals/Ratings**

Listing: UL Listed

CSA Certified

ANC Cooling

Isolation Transformer

##### **Special Orders- Requirements**

**Enclosure Material:** NEMA Type 3R Heavy Duty Ventilated

Contact us for special requirements

**Finish:** ANSI 61 Grey, UL50 Finish

**Toll Free:** 1-800-369-6671

**Dimensions:** 10.02"H x 5.40"W x 5.13"D

**Intl:** 1-214-616-6180

**Weight:** 24 lb

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**-Scroll Down to Purchase-**

This product does not qualify for free shipping.

Part #: MT-ISX-FP-1P-240V-1KVA-120V-N3R (222535)







Links (Click on the below items to view):

- [Hi-Res Image 1- Isolation Transformer](#)
- [Hi-Res Image 2- Isolation Transformer](#)
- [Hi-Res Image 3- Isolation Transformer](#)
- [Hi-Res Image 4- Isolation Transformer](#)